



MARINE









INDEX

Introduction	4
Application examples	5
Sailing yacht 'ecolution'	6
Motor yacht 'Sunseeker'	8
The Green Miles	10
Systems	12
Accessories	16
Technical information	19
About Victron Energy	86



INTRODUCTION

Marine market

Whether you sail for fun or on a professional basis, it is of the utmost importance to have a reliable power supply for all the electrical equipment to properly function, even in the middle of the sea. Victron Energy offers a broad range of products that are extremely suitable for your onboard power system.

Our products are being used in many different kinds of vessels: sailing yachts, cruise ships, sloops, tugboats, motor boats and container ships. We proudly present you our modern translation for freedom and independence. Energy. Anytime. Anywhere.











APPLICATION EXAMPLES









SAILING YACHT 'ECOLUTION'



Generating energy from water, wind and sun

The Ecolution is a 26 meter long sailing yacht, equipped with many sustainable techniques. During sailing the yacht develops substantial power, of which a part can be tapped without imposing significant reduction of sailing qualities. Two propellers are placed between the rudders of the vessel not only for propulsion but also for generating energy. The use of solar energy on the yacht is still in development.

Robust back-up system from Victron Energy

A safe and smart battery system has been designed by Victron specialist Johannes Boonstra. The energy generated by the Ecolution will be stored in 120 Victron batteries. With a total weight of 10.000 kg, the batteries will replace the use of conventional lead-ballast. The batteries are connected to a 24V Centaur charger and several Quattro inverters/chargers from Victron Energy. Wubbo Ockels is very happy with the system: 'It is a great back- up system, even when the central system fails there will still be an extra back-up'.





SAILING YACHT 'ECOLUTION'



The drive system is highly redundant and consists of two identical "strings' of a mechanically coupled (bio) Yanmar diesel engine (55kW), a 20kW electrical motor/generator, a gearbox and a 'camber-adaptive' propeller.

The sections I, II and III can be detached by couplings. Electrical power generation and electrical propulsion is provided by section I and II, while III and II provides a backup diesel generator function. Section I and III provides direct diesel propulsion.





MOTOR YACHT 'SUNSEEKER'



Sunseeker International, UK's leading motor yacht builder, uses MultiPlus inverter/chargers. The MultiPlus provides inverter power, battery charging, power management and UPS on their 82-94 foot yacht model range. While the yacht is in "silent running" mode, for instance when the yacht is at anchor, the inverter supplies power for entertainment and refrigeration. The UPS functionality of the MultiPlus ensures that there is a seamless transfer between shore power, generator power and inverter only operation. When mains power is available, the unit provides optimised battery charging. Any overload of the mains or generator will be prevented by using the additional power from the batteries, a feature called PowerAssist.





MOTOR YACHT 'SUNSEEKER'



Schematic overview of the installation in the Predator 84, Sunseeker.





THE GREEN MILES



The Netherlands: 'The Green Miles', green project for blue oceans

The Green Miles was started to create awareness among the general public for the problems of our oceans. In addition, The Green Miles wants to inspire people to interact with the world and the oceans in a green way. The Green Miles is a project in which Arjen van Eijk and Florian Dirkse sailed around the world in two years, raising awareness on ocean climate. Victron Energy backs the Green Miles' aims and is sponsoring the project by providing an on-board sustainable energy supply. Green products by Victron Energy are regularly used in remote places around the world to guarantee an independent energy supply. The energy provided on board of the Green Miles will therefore be sustainable as well as... comfortable!

Green sailing

The Green Miles' sustainable use of windpower to sail the world means there will be minimal use of fossil fuels and almost zero emissions. The yacht has also been adapted in several key areas. There are quite a few solar panels on board. A wind turbine provides additional energy. A waste disposal system means no harmful refuse needs to be thrown overboard. Green waste will be pulped so that sea creatures are able to feed on it. The boat has been fitted with a saltwater pump to prevent waste of drinking water, and energy-saving LED-lighting has been installed. The motor will only be used sparingly.





THE GREEN MILES



Schematic overview of the installation in 'The Green Miles'.







1. Simple system with only DC consumers

The battery charger charges the battery and functions as a power supply for the consumers.



2. System with inverter

This system contains an inverter to ensure a supply of 230VAC at all times. Many charger models have three outputs which allow for several battery groups to be charged separately.





Batteries

PowerAssist – boosting the capacity of shore or generator power

This unique Victron feature allows the MultiPlus to supplement the capacity of the shore or generator power. Where peak power is so often required only for a limited period, the MultiPlus will make sure that insufficient shore or generator power is immediately compensated with power from the battery. When the load reduces, the spare power is used to recharge the battery bank.

It is therefore no longer necessary to size a generator on the maximum peak load. Use the most efficient size generator instead.

Note: this feature is available in both the MultiPlus and the Quattro.

3. Multi-functional

The MultiPlus is a charger and inverter in one. It can function as an UPS (Uninterruptable Power Supply) to ensure power supply when the input power source fails. The MultiPlus also offers several other functional advantages such as PowerControl and PowerAssist.

MultiPlus vs Quattro

The MultiPlus and Quattro products play a central role in both AC and DC systems. They are both powerful battery chargers and inverters in one box.

The amount of available AC sources is the deciding factor when choosing between the Quattro and the Multi.

The big difference is that a Quattro can take two AC sources, and switch between them based on intelligent rules. It has a built-in transferswitch. The MultiPlus can take only one AC source.



4. System with generator

The Quattro has the same functions as the MultiPlus, but with an extra additon: a transfer system which can be directly connected to shore power and a generator.





5. Using a DC Generator

In this MultiPlus-based system example the generator directly charges the batteries and/or feeds the inverters. This system offers a lot of advantages such as weight reduction and comfort.



6. Using an AC Generator

This system example is based on a Quattro, which forms the heart of the system. Depending on how high the demand for power is, the Quattro will choose between battery- shore- and generator power.





Batteries

7. Parallel system Our inverters, Multi's and Quattro's can be paralleled to meet higher power requirements. A simple setting with our VEConfigure configuration software is sufficient.



8. Three-phase system

Similar to connecting units in parallel they can also be connected in split-phase and three-phase configurations.



ACCESSORIES

Our systems are comprised of various components. Some of which are specifically designed for specific markets. Other Victron components are applicable for a wide range of applications. You are able to find the specifications and other detailed information about these components in the 'Technical Information' section.



Battery Monitor

Key tasks of the Victron Battery Monitor are measuring charge and discharge currents as well as calculating the state-of-charge and time-togo of a battery. An alarm is sent when certain limits are exceeded (such as an excessive discharge). It is also possible for the battery monitor to ex change data with the Victron Global Remote. This includes sending alarms.



Victron Global Remote 2

Monitoring from a large distance is possible with the Victron Global Remote 2. The Global Remote 2 is a modem which sends text messages to mobile phones. These messages contain information about the status of a system as well as warnings and alarms. The Global Remote 2 also logs various types of data coming from Victron Battery Monitors, Multi's, Quattro's and Inverters. Consequently this data is sent to a website via a GPRS-connection. This enables you to access the read-outs remotely, where and whenever you like.



Ethernet Remote

The Ethernet Remote is similar to the Global Remote. The difference is that the Ethernet Remote has a LAN-connection. A special cable can be used to connect the Ethernet Remote directly to an existing internet connection.





Digital Multi Control Panel GX

With this panel you are able to remotely monitor and control Multiplus and Quattro systems. A simple turn of the button can limit the power supply of for example a generator and/or shore-side current. The setting range is up to 200A.

Blue Power Panel

It can be difficult to maintain a clear overview of your system as it grows larger. This is however not the case with a Blue Power Panel. Thanks to its clear display and intuitive control it enables you to easily monitor and control all devices connected to VE.Net and VE.Bus. Examples are Multi's, Quattro's and the VE.Net Battery Controller, which keeps track of the status of your battery bank.

ACCESSORIES



FILAX 2 Transfer switch

Filax 2: the ultra fast transfer switch

The Filax has been designed to switch sensitive loads, such as computers or modern entertainment equipment from one AC source to another. The priority source typically is the mains, a generator or shore power. The alternate source typically is an inverter.

Transfer switches 5kVA and 10kVA

The Transfer Switch is an automatic switching device between two different AC sources. Between generator and the grid, between an inverter and the grid or between the generator and an inverter.

BatteryProtect (Models: BP-40i, BP-60i, BP-200i)

The BatteryProtect disconnects the battery from non-essential loads before it is completely discharged (which would damage the battery) or before it has insufficient power left to crank the engine.

Alternators, charge regulators and more

- Superior solutions for charging large banks with one or more alternators.
- Compact and fully isolated high output alternators.
- Unsurpassed installation flexibility.
- 'Smart ready' internal regulation (6-series only): the internal constant-voltage regulator does not need to be removed when connecting an intelligent external regulator. The internal regulator remains available as a backup if ever the external regulator were to fail.
- The intelligent regulators are completely encapsulated: waterproof, shockproof and ignition protected.
- Parallel operation of 2 alternators possible with the 'Centerfielder' module.





Shore power cable

- Waterproof Shore Power Cable and Inlet IP67
- Moulded Plug and Connector
- Power indication LED
- Protection Cap
- Stainless Steel Inlet

ESP system panel

The new ESP panel system provides a contemporary designed range of panels that cover the core engineering systems. The main system panel is the heart of the range. This provides AC and DC monitoring, Multi control and backlight control. Additional panels include AC and DC circuit breaker panels, a general control panel, a VE Net panel.





17

Note: for our newest datasheets please refer to our website: www.victronenergy.com

13

194

1.40



Phoenix inverters 180VA - 1200VA 120V and 230V	20
Phoenix inverters 1200VA - 5000VA 230V	22
MultiPlus inverter/charger 800VA - 5kVA 230V	24
Quattro inverter/charger 3kVA - 10kVA 230V	26
MultiPlus inverter/charger 2kVA and 3kVA 120V	28
Quattro inverter/charger 3kVA and 5kVA 120V	30
Blue Power battery charger IP20	32
Blue Power battery charger IP20 180 VAC - 265 VAC	33
Blue Power battery charger waterproof IP65	34
Centaur charger 12/24V	36
Phoenix battery charger 12/24V	38
Skylla-i battery charger 24V	40
Skylla-TG charger 24/48V 230V	42
Skylla-TG charger 24V 9 <mark>0-265</mark> V GL approved	44
Skylla-TG 24/30 and 24/50 GMDSS	46
Isolation transformers	50
Orion DC/DC converters	52
Blue Power panel	54
Cyrix-i 12/24V 120A and 225A	55
Cyrix-i 200A-400A 12/24V and 24/48V	56
Victron Global Remote 2 and Victron Ethernet Remote	58
Precision battery monitoring	60
Argo diode battery isolators	62
Argo FET battery isolators	63
BlueSolar charge controllers MPPT 70/15	64
BlueSolar charge controllers MPPT 150/70	65
BlueSolar charge controllers	66
12,8 Volt Lithium iron phosphate batteries	68
BMS 12/200 for 12,8 Volt lithium iron phosphate batteries	70
24V 180Ah Lithium-ion battery and Lynx-ion	72
Ion control	74
Gel and AGM batteries	78
BlueSolar monocrystalline panels	82
BlueSolar polycrystalline panels	83
MultiPlus principle	84



PHOENIX INVERTERS 180VA - 1200VA 120V AND 230V



Phoenix Inverter 12/180



Phoenix Inverter 12/800 with Schuko socket

SinusMax – Superior engineering

Developed for professional duty, the Phoenix range of inverters is suitable for the widest range of applications. The design criteria have been to produce a true sine wave inverter with optimized efficiency but without compromise in performance. Employing hybrid HF technology, the result is a top quality product with compact dimensions, light in weight and capable of supplying power, problem-free, to any load.

Extra start-up power

A unique feature of the SinusMax technology is very high start-up power. Conventional high frequency technology does not offer such extreme performance. Phoenix inverters, however, are well suited to power up difficult loads such as computers and low power electric tools.

To transfer the load to another AC source: the automatic transfer switch

For our lower power models we recommend the use of our Filax Automatic Transfer Switch. The Filax features a very short switchover time (less than 20 miliseconds) so that computers and other electronic equipment will continue to operate without disruption.

LED diagnosis

Please see manual for a description.

Remote on/off switch

Connector for remote on off switch available on all models.

Remote control panel (750VA model only)

Connects to the inverter with a RJ12 UTP cable (length 3 meter, included).

DIP switch for 50/60Hz selection (750VA model only)

DIP switches for Power Saving Mode (750VA model only)

When operating in Power Saving Mode, the no-load current is reduced to 1/3 of nominal. In this mode the inverter is switched off in case of no load or very low load, and switches on every two seconds for a short period. If the output current exceeds a set level. The inverter will continue to operate. If not, the inverter will shut down again. The on/off level can be set from 15W to 85W with DIP switches.

Available with different output sockets

Please see pictures below.

Phoenix Inverter 12/800

with Schuko socket



Phoenix Inverter 12/350 with IEC-320 sockets



Phoenix Inverter 12/800 with IEC-320 socket



Phoenix Inverter 12/180 with Schuko socket



Phoenix Inverter 12/800 with BS 1363 socket



Phoenix Inverter 12/800 with AN/NZS 3112 socket



Phoenix Inverter 12/180 with Nema 5-15R sockets



Phoenix Inverter 12/800 with Nema 5-15R socket



PHOENIX INVERTERS 180VA - 1200VA 120V AND 230V

12 Volt	12/180	12/350		12/800	12/1200	
Phoenix inverter 24 voit 48 Volt	24/180	48/350	48/750	48/800	48/1200	
Cont. AC power at 25 °C (VA) (3)	180	350	750	800	1200	
Cont. power at 25 °C / 40 °C (W)	175 / 150	300 / 250	700 / 650	700 / 650	1000 / 900	
Peak power (W)	350	700	1400	1600	2400	
Output AC voltage / frequency (4)		110VAC or 23	0VAC +/- 3% 50Hz or 60Hz	z +/- 0,1%		
Input voltage range (V DC)	10,5	5 - 15,5 / 21,0 - 31,0 / 42,0 - 62	,0	9,2 - 17,3 / 18,4 -	34,0 / 36,8 - 68,0	
Low battery alarm (V DC)		11,0 / 22 / 44		10,9 / 21	,8 / 43,6	
Low battery shut down (V DC)		10,5 / 21 / 42		9,2 / 18,	4 / 36,8	
Low battery auto recovery (V DC)		12,5 / 25 / 50		12,5 / 2	25 / 50	
Max. efficiency (%)	87 / 88	89 / 89/ 90	94	91 / 93 / 94	92 / 94 / 94	
Zero-load power (W)	2,6 / 3,8	3,1 / 5,0 / 6,0	13	6/5/4	6/5/6	
Zero-load power in search mode	n. a.	n. a.	5	2	2	
Protection (2)			a - e			
Operating temperature range		-40 to	+50°C (fan assisted cooling	ı)		
Humidity (non condensing)	max 95%					
ENCLOSURE						
Material & Colour		al	uminium (blue Ral 5012)			
Battery-connection	1)	1)	Screw terminals	1)	1)	
Standard AC outlets		230V: IEC-320 (IE	C-320 plug included), CEE 7 120V: Nema 5-15R	7/4 (Schuko)		
Other outlets (at request)		B: AN/NZS	5 1363 (United Kingdom) 5 3112 (Australia, New Zeala	nd)		
Protection category			IP 20			
Weight (kg / lbs)	2,7 / 5,4	3,5 / 7,7	2,7 / 5,4	6,5 / 14.3	8,5 / 18.7	
Dimensions (hxwxd in mm) (hxwxd in inches)	72x132x200 2.8x5.2x7.9	72x155x237 2.8x6.1x9.3	72x180x295 2.8x7.1x11.6	108x165x305 4.2x6.4x11.9	108x165x305 4.2x6.4x11.9	
		ACCESSORIES				
Remote control panel	n. a.	n. a.	Optional	n. a.	n. a.	
Remote on-off switch	Two pole	connector	RJ12 plug	Two pole	connector	
Automatic transfer switch			Filax			
		STANDARDS				
Safety			EN 60335-1			
Emission Immunity	EN55014-1 / EN 55014-2/ EN 61000-6-2 / EN 61000-6-3					
 Battery cables of 1.5 meter (12/180 with cigarette plug) Protection key: a) output short circuit b) overload 	3) Non linear load, crest factor 3:1 4) Frequency can be set by DIP switch (48V/750VA model only)					

- c) battery voltage too high d) battery voltage too low
- e) temperature too high



Battery Alarm

An excessively high or low battery voltage is indicated by an audible and visual alarm, and a relay for remote signalling.



BMV Battery Monitor

The BMV Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current. Besides this, the software includes complex calculation algorithms to exactly determine the state of charge of the battery. The BMV selectively displays battery voltage, current, consumed Ah or time to go. The monitor also stores a host of data regarding performance and use of the battery.



PHOENIX INVERTERS 1200VA - 5000VA 230V



Phoenix Inverter 24/5000



Phoenix Inverter Compact 24/1600

SinusMax - Superior engineering

Developed for professional duty, the Phoenix range of inverters is suitable for the widest range of applications. The design criteria have been to produce a true sine wave inverter with optimised efficiency but without compromise in performance. Employing hybrid HF technology, the result is a top quality product with compact dimensions, light in weight and capable of supplying power, problem-free, to any load.

Extra start-up power

A unique feature of the SinusMax technology is very high start-up power. Conventional high frequency technology does not offer such extreme performance. Phoenix inverters, however, are well suited to power up difficult loads such as refrigeration compressors, electric motors and similar appliances.

Virtually unlimited power thanks to parallel and 3-phase operation capability

Up to 6 units inverters can operate in parallel to achieve higher power output. Six 24/5000 units, for example, will provide 24kW / 30kVA output power. Operation in 3-phase configuration is also possible.

To transfer the load to another AC source: the automatic transfer switch

If an automatic transfer switch is required we recommend using the MultiPlus inverter/charger instead. The switch is included in these products and the charger function of the MultiPlus can be disabled. Computers and other electronic equipment will continue to operate without disruption because the MultiPlus features a very short switchover time (less than 20 milliseconds).

Computer interface

All models have a RS-485 port. All you need to connect to your PC is our MK2 interface (see under accessories). This interface takes care of galvanic isolation between the inverter and the computer, and converts from RS-485 to RS-232. A RS-232 to USB conversion cable is also available. Together with our VEConfigure software, which can be downloaded free of charge from our website, all parameters of the inverters can be customised. This includes output voltage and frequency, over and under voltage settings and programming the relay. This relay can for example be used to signal several alarm conditions, or to start a generator. The inverters can also be connected to VENet, the new power control network of Victron Energy, or to other computerised monitoring and control systems.

New applications of high power inverters

The possibilities of paralleled high power inverters are truly amazing. For ideas, examples and battery capacity calculations please refer to our book "Energy Unlimited" (available free of charge from Victron Energy and downloadable from <u>www.victronenergy.com</u>).



Phoenix battery charger



PHOENIX INVERTERS 1200VA - 5000VA 230V

Phoenix Inverter	C12/1200 C24/1200	C12/1600 C24/1600	C12/2000 C24/2000	12/3000 24/3000 48/3000	24/5000 48/5000			
Parallel and 3-phase operation			Yes					
	INVERTER							
Input voltage range (V DC)		9	,5 – 17V 19 – 33V 38 – 66	5V				
Output		Output voltage	e: 230 VAC ±2% Frequency:	50 Hz ± 0,1% (1)				
Cont. output power at 25 9 C (VA) (2)	1200	1600	2000	3000	5000			
Cont. output power at 25 $^{\circ}$ C (W)	1000	1300	1600	2500	4500			
Cont. output power at 40 ^o C (W)	900	1200	1450	2200	4000			
Peak power (W)	2400	3000	4000	6000	10000			
Max. efficiency 12/ 24 /48 V (%)	92 / 94	92 / 94	92 / 92	93 / 94 / 95	94 / 95			
Zero-load power 12 / 24 / 48 V (W)	8/10	8/10	9/11	15 / 15 / 16	25 / 25			
Zero-load power in AES mode (W)	5/8	5 / 8	7/9	10/10/12	20 / 20			
Zero-load power in Search mode (W)	2/3	2/3	3/4	4/5/5	5/6			
		GENERAL						
Programmable relay (3)			Yes					
Protection (4)			a - g					
VE.Bus communication port		For parallel and three phas	e operation, remote monito	ring and system integration				
Remote on-off			Yes					
Common Characteristics		Operating temper Hum	ature range: -40 to +50 ºC (fa idity (non condensing): max	an assisted cooling) < 95%				
		ENCLOSURE						
Common Characteristics		Material & Colour: alur	ninum (blue RAL 5012) Pro	otection category: IP 21				
Battery-connection	battery cables of 1	.5 meter included	M8 bolts	2+2 M	8 bolts			
230 V AC-connection	G-ST18	3i plug	Spring-clamp	Screw te	erminals			
Weight (kg)	1	0	12	18	30			
Dimensions (hxwhd in mm)	375x2	14x110	520x255x125	362x258x218	444x328x240			
STANDARDS								

Saf	fety		EN 60335-1
Em	nission Immunity		EN 55014-1 / EN 55014-2
1) C 2) N 3) P gr st	Can be adjusted to 60Hz and to 240V Von linear load, crest factor 3:1 Programmable relay that can a.o. be set for eneral alarm, DC undervoltage or genset tart/stop function. AC rating: 230V/4A DC rating: 4a up to 35VDC, 1A up to 60VDC	 4) Protection key: a) output short circuit b) overload c) battery voltage too high d) battery voltage too low e) temperature too high f) 230 V AC on inverter output 	



Phoenix Inverter Control

This panel can also be used on a MultiPlus inverter/charger when an automatic transfer switch but no charger function is desired. The brightness of the LEDs is automatically reduced during night time.

Computer controlled operation and monitoring

Several interfaces are available:

g) input voltage ripple too high

- MK2.2 VE.Bus to RS232 converter
 Connects to the RS232 port of a computer (see 'A guide to VEConfigure')
 MK2-USB VE.Bus to USB converter
- Connects to a USB port (see 'A guide to VEConfigure')
- VE.Net to VE.Bus converter
- Interface to VE.Net (see VE.Net documentation)
- VE.Bus to NMEA 2000 converter
- Victron Global Remote
- The Global Remote is a modem which sends alarms, warnings and system status reports to cellular phones via text messages (SMS). It can also log data from Victron Battery Monitors, Multi's, Quattro's and Inverters to a website through a GPRS connection. Access to this website is free of charge.
- Victron Ethernet Remote To connect to Ethernet.

BMV Battery Monitor

The BMV Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge / discharge current. Besides this, the software includes complex calculation algorithms, like Peukert's formula, to exactly determine the state of charge of the battery. The BMV selectively displays battery voltage, current, consumed Ah or time to go. The monitor also stores a host of data regarding performance and use of the battery.

Several models available (see battery monitor documentation).



MULTIPLUS INVERTER/CHARGER 800VA - 5KVA 230V

Lithium Ion battery compatible



MultiPlus 24/3000/70



MultiPlus Compact 12/2000/80

Multi-functional, with intelligent power management

The MultiPlus is a powerful true sine wave inverter, a sophisticated battery charger that features adaptive charge technology, and a high-speed AC transfer switch in a single compact enclosure. Next to these primary functions, the MultiPlus has several advanced features, as outlined below.

Two AC Outputs

The main output has no-break functionality. The MultiPlus takes over the supply to the connected loads in the event of a grid failure or when shore/generator power is disconnected. This happens so fast (less than 20 milliseconds) that computers and other electronic equipment will continue to operate without disruption. The second output is live only when AC is available on one of the inputs of the MultiPlus. Loads that should not discharge the battery, like a water heater for example, can be connected to this output (second output available on models rated at 3kVA and more).

Virtually unlimited power thanks to parallel operation

Up to 6 Multi's can operate in parallel to achieve higher power output. Six 24/5000/120 units, for example, will provide 25 kW / 30 kVA output power with 720 Amps charging capacity.

Three phase capability

In addition to parallel connection, three units of the same model can be configured for three-phase output. But that's not all: up to 6 sets of three units can be parallel connected for a huge 75 kW / 90 kVA inverter and more than 2000 Amps charging capacity.

PowerControl - Dealing with limited generator, shore side or grid power

The MultiPlus is a very powerful battery charger. It will therefore draw a lot of current from the generator or shore side supply (nearly 10A per 5kVA Multi at 230VAC). With the Multi Control Panel a maximum generator or shore current can be set. The MultiPlus will then take account of other AC loads and use whatever is extra for charging, thus preventing the generator or shore supply from being overloaded.

PowerAssist - Boosting the capacity of shore or generator power

This feature takes the principle of PowerControl to a further dimension. It allows the MultiPlus to supplement the capacity of the alternative source. Where peak power is so often required only for a limited period, the MultiPlus will make sure that insufficient shore or generator power is immediately compensated for by power from the battery. When the load reduces, the spare power is used to recharge the battery.

Four stage adaptive charger and dual bank battery charging

The main output provides a powerful charge to the battery system by means of advanced 'adaptive charge' software. The software fine-tunes the three stage automatic process to suit the condition of the battery, and adds a fourth stage for long periods of float charging. The adaptive charge process is described in more detail on the Phoenix Charger datasheet and on our website, under Technical Information. In addition to this, the MultiPlus will charge a second battery using an independent trickle charge output intended for a main engine or generator starter battery (trickle charge output available on 12V and 24V models only).

System configuring has never been easier

After installation, the MultiPlus is ready to go.

If settings have to be changed, this can be done in a matter of minutes with a new DIP switch setting procedure. Even parallel and 3-phase operation can be programmed with DIP switches: no computer needed! Alternatively, VE.Net can be used instead of the DIP switches.

And sophisticated software (VE.Bus Quick Configure and VE.Bus System Configurator) is available to configure several new, advanced, features.

PowerAssist with 2x MultiPlus in parallel



Five parallel units: output power 25 kVA





MULTIPLUS INVERTER/CHARGER 800VA - 5kVA 230V

12 VoltMultiPlus24 Volt	C 12/800/35 C 24/ 800/16	C 12/1200/50 C 24/1200/25	C 12/1600/70 C 24/1600/40	C 12/2000/80 C 24/2000/50	12/3000/120 24/3000/70	24/5000/120
48 Volt					48/3000/35	48/5000/70
PowerControl	Yes	Yes	Yes	Yes	Yes	Yes
PowerAssist	Yes	Yes	Yes	Yes	Yes	Yes
Transfer switch (A)	16	16	16	30	16 or 50	50
Parallel and 3-phase operation	Yes	Yes	Yes	Yes	Yes	Yes
Input voltage range (V DC)		INVI	95_17V 19_	- 33 V 38 - 66 V		
Output		Output vol	tage: 230 VAC + 2%	Frequency: 50 F	47 + 0.1% (1)	
Controut power at 25 °C (VA) (3)	800	1200	1600	2000	3000	5000
Controutput power at 25 °C (W)	700	1000	1300	1600	2500	4500
Controutput power at 40 $^{\circ}$ C (W)	650	900	1200	1450	2200	4000
Peak power (W)	1600	2400	3000	4000	6000	10.000
Maximum efficiency (%)	92 / 94	93 / 94	93/94	93 / 94	93 / 94 / 95	94 / 95
Zero-load power (W)	8/10	8/10	8/10	9/11	15/15/16	25/25
Zero load power in AFS mode (W)	5/8	5/8	5/8	7/9	10/10/12	20/20
Zero load power in Search mode (W)	2/3	2/3	2/3	3/4	4/5/5	5/6
	_, _	CHA	RGER			
AC Input		Input voltage range	: 187-265 VAC Inp	ut freguency: 45 – 65 H	Iz Power factor: 1	
Charge voltage 'absorption' (V DC)		1 3 3	14,4 / 28	8,8 / 57,6		
Charge voltage 'float' (V DC)			13,8 / 2	7,6 / 55,2		
Storage mode (V DC)			13,2 / 20	6,4 / 52,8		
Charge current house battery (A) (4)	35 / 16	50 / 25	70 / 40	80 / 50	120 / 70 / 35	120 / 70
Charge current starter battery (A)			4 (12V and 24	V models only)		
Battery temperature sensor			у	es		
		GEN	IERAL			
Auxiliary output (5)	n. a.	n. a.	n.a.	n. a.	Yes (16A)	Yes (25A)
Programmable relay (6)			Y	es		
Protection (2)			a	- g		
VE.Bus communication port		For parallel and th	nree phase operation, re	emote monitoring and	system integration	
General purpose com. port (7)	n. a.	n. a.	n. a.	n.a.	Yes (8)	Yes
Remote on-off			Y	es		
Common Characteristics	O	perating temp. range: -4	40 to +50°C (fan assiste	d cooling) Humidity (non condensing): max	95%
		ENCL	OSURE			
Common Characteristics		Material & Colour	r: aluminium (blue RAL	5012) Protect	tion category: IP 21	
Battery-connection	b	attery cables of 1.5 met	er	M8 bolts	Four M8 bolts (2 plus	and 2 minus connections)
230 V AC-connection		G-ST18i connector		Spring-clamp	Screw terminal	s 13 mm² (6 AWG)
Weight (kg)	10	10	10	12	18	30
Dimensions (hxwxd in mm)		375x214x110		520x255x125	362x258x218	444x328x240
		STAN	DARDS			
Safety			EN 60335-1, E	EN 60335-2-29		
Emission, Immunity	EN55014-1, EN 55014-2, EN 61000-3-3					
Automotive Directive			2004/	104/EC		
 Can be adjusted to 60 HZ; 120 V 60 Hz on request Protection key: a) output short circuit b) overload c) battery voltage too high d) battery voltage too low e) temperature too high f) 20 VAC on inverter output a) input voltage too high 	 3) Non linear load, crest factor 3:1 4) At 25 °C ambient 5) Switches off when no external AC source available 6) Programmable relay that can a. o. be set for general alarm, DC undervoltage or geneset start/stop function AC rating: 230V/4A DC rating: 4A up to 35VDC, 1A up to 60VDC 7) A. o. to communicate with a Lithium Ion battery BMS 					



Digital Multi Control

A convenient and low cost solution for remote monitoring, with a rotary knob to set Power Control and Power Assist levels.



Blue Power Panel Connects to a Multi or Quattro and all VE.Net devices, in particular the VE.Net Battery Controller. Graphic display of currents and voltages.



Computer controlled operation and monitoring

- Several interfaces are available: - MK2.2 VE.Bus to RS232 converter
- Connects to the RS232 port of a computer (see 'A guide to VEConfigure') - MK2-USB VE.Bus to USB converter
- Connects to a USB port (see 'A guide to VEConfigure')
- VE.Net to VE.Bus converter
- Interface to VE.Net (see VE.Net documentation)
- VE.Bus to NMEA 2000 converter - Victron Global Remote

The Global Remote is a modem which sends alarms, warnings and system status reports to cellular phones via text messages (SMS). It can also log data from Victron Battery Monitors, Multi's, Quattro's and Inverters to a website through a GPRS connection. Access to this website is free of charge. - Victron Ethernet Remote

To connect to Ethernet.

BMV Battery Monitor

The BMV Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current. Besides this, the software includes complex calculation algorithms, like Peukert's formula, to exactly determine the state of charge of the battery. The BMV selectively displays battery voltage, current, consumed Ah or time to go. The monitor also stores a host of data regarding performance and use of the battery.

Several models available (see battery monitor documentation).



QUATTRO INVERTER/CHARGER 3kVA - 10kVA 230V

Lithium Ion battery compatible

Two AC inputs with integrated transfer switch

The Quattro can be connected to two independent AC sources, for example shore-side power and a generator, or two generators. The Quattro will automatically connect to the active source.

Two AC Outputs

The main output has no-break functionality. The Quattro takes over the supply to the connected loads in the event of a grid failure or when shore/generator power is disconnected. This happens so fast (less than 20 milliseconds) that computers and other electronic equipment will continue to operate without disruption. The second output is live only when AC is available on one of the inputs of the Quattro. Loads that should not discharge the battery, like a water heater for example, can be connected to this output.

Virtually unlimited power thanks to parallel operation

Up to 10 Quattro units can operate in parallel. Ten units 48/10000/140, for example, will provide 90kW / 100kVA output power and 1400 Amps charging capacity.

Three phase capability

Three units can be configured for three-phase output. But that's not all: up to 10 sets of three units can be parallel connected to provide 270kW / 300kVA inverter power and more than 4000A charging capacity.

PowerControl - Dealing with limited generator, shore-side or grid power

The Quattro is a very powerful battery charger. It will therefore draw a lot of current from the generator or shore side supply (16A per 5kVA Quattro at 230VAC). A current limit can be set on each AC input. The Quattro will then take account of other AC loads and use whatever is spare for charging, thus preventing the generator or shore supply from being overloaded.

PowerAssist - Boosting shore or generator power

This feature takes the principle of PowerControl to a further dimension allowing the Quattro to supplement the capacity of the alternative source. Where peak power is so often required only for a limited period, the Quattro will make sure that insufficient shore or generator power is immediately compensated for by power from the battery. When the load reduces, the spare power is used to recharge the battery.

Solar energy: AC power available even during a grid failure

The Quattro can be used in off grid as well as grid connected PV and other alternative energy systems.

System configuring has never been easier

After installation, the Quattro is ready to go.

If settings have to be changed, this can be done in a matter of minutes with a new DIP switch setting procedure. Even parallel and 3-phase operation can be programmed with DIP switches: no computer needed! Alternatively, VE.Net can be used instead of the DIP switches.

And sophisticated software (VE.Bus Quick Configure and VE.Bus System Configurator) is available to configure several new, advanced, features.





Ouattro 48/5000/70-100/100



Ouattro 24/3000/70-50/30



QUATTRO INVERTER/CHARGER 3kVA - 10kVA 230V

	12/2000/120 50/20	12/5000/220 100/100				
Quattro	12/3000/120-50/30	24/5000/120-100/100	24/8000/200-100/100			
Quartio	24/3000/70 30/30	48/5000/70-100/100	48/8000/110-100/100	48/10000/140-100/100		
PowerControl / PowerAssist	Yes					
Integrated Transfer switch		Yes				
AC inputs (2x)	Input v	oltage range: 187-265 VAC Input fre	equency: 45 – 65 Hz Power factor	: 1		
Maximum feed through current (A)	50 / 30	2x100	2x100	2x100		
		INVERTER				
Input voltage range (V DC)		9,5 – 17V 19 – 33V	38 – 66V			
Output (1)		Output voltage: 230 VAC \pm 2%	Frequency: 50 Hz ± 0,1%			
Cont. output power at 25 °C (VA) (3)	3000	5000	8000	10000		
Cont. output power at 25 °C (W)	2500	4500	7000	9000		
Cont. output power at 40 °C (W)	2200	4000	6300	8000		
Peak power (W)	6000	10000	16000	20000		
Maximum efficiency (%)	93 / 94	94 / 94 / 95	94 / 96	96		
Zero-load power (W)	15 / 15	25 / 25 / 25	30 / 35	35		
Zero load power in AES mode (W)	10 / 10	20 / 20 / 20	25 / 30	30		
Zero load power in Search mode (W)	4 / 5	5/5/6	8 / 10	10		
		CHARGER				
Charge voltage 'absorption' (V DC)	14,4 / 28,8	14,4 / 28,8 / 57,6	28,8 / 57,6	57,6		
Charge voltage 'float' (V DC)	13,8 / 27,6	13,8 / 27,6 / 55,2	27,6 / 55,2	55,2		
Storage mode (V DC)	13,2 / 26,4	13,2 / 26,4 / 52,8	26,4 / 52,8	52,8		
Charge current house battery (A) (4)	120 / 70	220 / 120 / 70	200 / 110	140		
Charge current starter battery (A)		4 (12V and 24V mo	odels only)			
Battery temperature sensor		Yes				
		GENERAL				
Auxiliary output (A) (5)	25	50	50	50		
Programmable relay (6)	1x	3x	3x	3x		
Protection (2)	-	a-g				
VE.Bus communication port	For para	llel and three phase operation, remo	e monitoring and system integrat	tion		
General purpose com. port (/)	IX	2X	2X	2X		
Common Characteristics	0-	res	ity (non condensing), may OE0(
Common characteristics	OF		ity (non condensing). max. 95%			
Common Characteristics	Mat	rerial & Colour: aluminium (blue BAL 5	(012) Protection category: IP 21			
Battery-connection	, inde	Four M8 bolts (2 plus and 2	minus connections)			
230 V AC-connection	Screw terminals 13 mm ² (6 AWG)	Bolts M6	Bolts M6	Bolts M6		
Weight (kg)	19	34 / 30 / 30	45/41	45		
Weight (kg)	13	470 x 350 x 280	13/11	15		
Dimensions (hxwxd in mm)	362 x 258 x 218	444 x 328 x 240	470 x 350 x 280	470 x 350 x 280		
· · ·		444 x 328 x 240				
		STANDARDS				
Safety		EN 60335-1, EN	60335-2-29			
Emission, Immunity	EN55	014-1, EN 55014-2, EN 61000-3-3, EN	61000-6-3, EN 61000-6-2, EN 6100	0-6-1		
1) Can be adjusted to 60 HZ; 120 V 60 Hz on	3) Non linear load, crest factor 3:1					
request	4) At 25 °C ambient 5) Switches off when no external A					
a) output short circuit	6) Programmable relay that can a. c	b. be set for general alarm,				
b) overload	DC undervoltage or genset start	/stop function				
c) battery voltage too high	AC rating: 230V/4A					
e) temperature too high	7) A. o. to communicate with a Lithi	up to 60VDC				
f) 230 VAC on inverter output	-,					
g) input voltage ripple too high						
			C. C. Starting			
			1000			
and a state of the						
			-0-	1		

Digital Multi Control Panel

A convenient and low cost solution for remote monitoring, with a rotary knob to set Power Control and Power Assist levels.



Blue Power Panel

Connects to a Multi or Ouattro and all VE.Net devices, in particular the VE.Net Battery Controller. Graphic display of currents and voltages.



Computer controlled operation and monitoring

Several interfaces are available:

- MK2.2 VE.Bus to RS232 converter
- Connects to the RS232 port of a computer (see 'A guide to VEConfigure') - MK2-USB VE.Bus to USB converter
- Connects to a USB port (see 'A guide to VEConfigure')
- VE.Net to VE.Bus converter
- Interface to VE.Net (see VE.Net documentation)
- VE.Bus to NMEA 2000 converter - Victron Global Remote
- The Global Remote is a modem which sends alarms, warnings and system status reports to cellular phones via text messages (SMS). It can also log data from Victron Battery Monitors, Multi's, Quattro's and Inverters to a website through

a GPRS connection. Access to this website is free of charge. - Victron Ethernet Remote

To connect to Ethernet.

BMV Battery Monitor

The BMV Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current. Besides this, the software includes complex calculation algorithms, like Peukert's formula, to exactly determine the state of charge of the battery. The BMV selectively displays battery voltage, current, consumed Ah or time to go. The monitor also stores a host of data regarding performance and use of the battery.

Several models available (see battery monitor documentation).



MULTIPLUS INVERTER/CHARGER 2KVA AND 3KVA 120V

Lithium Ion battery compatible



MultiPlus 24/3000/70



MultiPlus Compact 12/2000/80

Multi-functional, with intelligent power management

The MultiPlus is a powerful true sine wave inverter, a sophisticated battery charger that features adaptive charge technology, and a high-speed AC transfer switch in a single compact enclosure. Next to these primary functions, the MultiPlus has several advanced features, as outlined below.

Two AC Outputs

The main output has no-break functionality. The MultiPlus takes over the supply to the connected loads in the event of a grid failure or when shore/generator power is disconnected. This happens so fast (less than 20 milliseconds) that computers and other electronic equipment will continue to operate without disruption. The second output is live only when AC is available on the input of the MultiPlus. Loads that should not discharge the

battery, like a water heater for example, can be connected to this output (second output available on models rated at 3kVA and more).

Virtually unlimited power thanks to parallel operation

Up to six Multi's can operate in parallel to achieve higher power output. Six 24/3000/70 units, for example, provide 15kW / 18kVA output power with 420 Amps of charging capacity.

Three phase capability

In addition to parallel connection, three units can be configured for three-phase output. But that's not all: with three strings of six parallel units a 45kW / 54kVA three phase inverter and 1260A charger can be built.

Split phase options

Two units can be stacked to provide 120-0-120V, and additional units can be paralleled up to a total of 6 units per phase, to supply up to 30kW / 36kVA of split phase power.

Alternatively, a split phase AC source can be obtained by connecting our autotransformer (see data sheet on www.victronenergy.com) to a 'European' inverter programmed to supply 240V / 60Hz.

PowerControl - Dealing with limited generator, shore side or grid power

The MultiPlus is a very powerful battery charger. It will therefore draw a lot of current from the generator or shore side supply (nearly 20A per 3kVA MultiPlus at 120VAC). With the Multi Control Panel a maximum generator or shore current can be set. The MultiPlus will then take account of other AC loads and use whatever is extra for charging, thus preventing the generator or shore supply from being overloaded.

PowerAssist - Boosting the capacity of shore or generator power

This feature takes the principle of PowerControl to a further dimension. It allows the MultiPlus to supplement the capacity of the alternative source. Where peak power is so often required only for a limited period, the MultiPlus will make sure that insufficient shore or generator power is immediately compensated for by power from the battery. When the load reduces, the spare power is used to recharge the battery.

Four stage adaptive charger and dual bank battery charging

The main output provides a powerful charge to the battery system by means of advanced 'adaptive charge' software. The software fine-tunes the three stage automatic process to suit the condition of the battery, and adds a fourth stage for long periods of float charging. The adaptive charge process is described in more detail on the Phoenix Charger datasheet and on our website, under Technical Information. In addition to this, the MultiPlus will charge a second battery using an independent trickle charge output intended for a main engine or generator starter battery.

System configuring has never been easier

After installation, the MultiPlus is ready to go.

If settings have to be changed, this can be done in a matter of minutes with a DIP switch setting procedure. Even parallel and 3-phase operation can be programmed with DIP switches: no computer needed! Alternatively, VE.Net can be used instead of the DIP switches.

And sophisticated software (VE.Bus Quick Configure and VE.Bus System Configurator) is available to configure several new, advanced, features.

PowerAssist with 2x MultiPlus in parallel

Five parallel units: output power 12,5 kW





MULTIPLUS INVERTER/CHARGER 2KVA AND 3KVA 120V

12 Volt	12/2000/80	12/3000/120			
MultiPlus 24 Volt	24/2000/50	24/3000/70			
PowerControl	Ye	25			
PowerAssist	Ye	95			
Transfer switch (A)	50	0			
Parallel and 3-phase operation	Ye	25			
	INVERTER				
Input voltage range (V DC)	9,5 – 17 V	19 – 33 V			
Output	Output voltage: 120 VAC ± 2%	Frequency: 60 Hz \pm 0,1% (1)			
Cont. output power at 75 °F (VA) (3)	2000	3000			
Cont. output power at 75 °F (W)	1600	2500			
Cont. output power at 100 °F (W)	1450	2200			
Peak power (W)	4000	6000			
Maximum efficiency (%)	92/94	93/94			
Zero-load power (W)	9/11	15/15			
Zero load power in AES mode (W)	//8	10/10			
Zero load power in Search mode (W)	3/4	4/5			
AClassit	CHARGER	framer an AF CELLE Deven factor 1			
AC input	Input voitage range: 95-140 VAC Input	Trequency: 45 – 65 Hz Power factor: 1			
Charge voltage absorption (VDC)	14,4 /	28,8			
Charge voltage float (VDC)	13,8/	27,0			
Storage mode (V DC)	13,2 / 26,4				
Charge current starter battery (A) (4)	80/50 120/70				
Patter temperature concer	4				
Battery temperature sensor	CENEDAL	3			
Auvilian output (5)		Vec (32A)			
Programmable relay (6)	Ves (1v)	Vec (32A)			
Protection (2)		0			
VE Bus communication port	For parallel and three phase operation, re	9 mote monitoring and system integration			
General purpose com port (7)	n a	Vec (2v)			
Remote on-off	Yest Yest	105 (2A)			
Common Characteristics	Operating temp_range: 0 - 120°E (fan assisted op	ooling) Humidity (non condensing): max 95%			
	ENCLOSURE	initially from contractioning, max 5575			
Common Characteristics	Material & Colour: aluminum (blue RAL	5012) Protection category: IP 21			
Battery-connection	M8 bolts	M8 bolts (2 plus and 2 minus connections)			
120 V AC-connection	Screw-terminal 6 AWG (13mm ²)	Screw-terminal 6 AWG (13mm ²)			
Weight	13kg 25 lbs	19kg 40 lbs			
Dimensions (hxwxd in mm and inches)	520x255x125 mm 20.5x10.0x5.0 inch	362x258x218 mm 14.3x10.2x8.6 inch			
	STANDARDS				
Safety	EN 60335-1, E	N 60335-2-29			
Emission Immunity	EN55014-1, EN 550	14-2, EN 61000-3-3			
1) Can be adjusted to 60 HZ; 120 V 60 Hz on i	equest 3) Non linear load, crest factor 3:1				
2) Protection key:	4) At 75 °F ambient				
a) output snort circuit b) overload	5) Switches off when no external AC source available				
c) battery voltage too high	o) Programmable relay that can a. o. be set for general alarm, DC undervoltage or genset start/stop function				
d) battery voltage too low	AC rating: 230V/4A				
e) temperature too high	DC rating: 4A up to 35VDC, 1A up to 60VDC				
g) input voltage ripple too high	/) A. o. to communicate with a Lithium Ion battery BMS				



Digital Multi Control

A convenient and low cost solution for remote monitoring, with a rotary knob to set Power Control and Power Assist levels.



Blue Power Panel Connects to a Multi or Quattro and all VE.Net devices, in particular the VE.Net Battery Controller. Graphic display of currents and voltages.





Computer controlled operation and monitoring

- Several interfaces are available: - MK2.2 VE.Bus to RS232 converter
- Connects to the RS232 port of a computer (see 'A guide to VEConfigure')
 MK2-USB VE.Bus to USB converter
- Connects to a USB port (see 'A guide to VEConfigure')
- VE.Net to VE.Bus converter
- Interface to VE.Net (see VE.Net documentation)
- VE.Bus to NMEA 2000 converter
- Victron Global Remote

The Global Remote is a modem which sends alarms, warnings and system status reports to cellular phones via text messages (SMS). It can also log data from Victron Battery Monitors, Multi's, Quattro's and Inverters to a website through a GPRS connection. Access to this website is free of charge.

- Victron Ethernet Remote To connect to Ethernet. BMV Battery Monitor

The BMV Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current. Besides this, the software includes complex calculation algorithms, like Peukert's formula, to exactly determine the state of charge of the battery. The BMV selectively displays battery voltage, current, consumed Ah or time to go. The monitor also stores a host of data regarding performance and use of the battery.



QUATTRO INVERTER/CHARGER 3KVA AND 5KVA 120V

Lithium Ion battery compatible

Two AC inputs with integrated transfer switch

The Quattro can be connected to two independent AC sources, for example shore-side power and a generator, or two generators. The Quattro will automatically connect to the active source.

Two AC Outputs

The main output has no-break functionality. The Quattro takes over the supply to the connected loads in the event of a grid failure or when shore/generator power is disconnected. This happens so fast (less than 20 milliseconds) that computers and other electronic equipment will continue to operate without disruption.

The second output is live only when AC is available on one of the inputs of the Quattro. Loads that should not discharge the battery, like a water heater for example, can be connected to this output.

Virtually unlimited power thanks to parallel operation

Up to 10 Quattro units can operate in parallel. Ten units 48/5000/70, for example, will provide 45kW / 50kVA output power and 700 Amps charging capacity.

Three phase capability

Three units can be configured for three-phase output. But that's not all: up to 10 sets of three units can be parallel connected to provide 135kW / 150kVA inverter power and more than 2000A charging capacity.

Split phase options

Two units can be stacked to provide 120-0-120V, and additional units can be paralleled up to a total of 6 units per phase, to supply up to 30kW / 36kVA of split phase power.

Alternatively, a split phase AC source can be obtained by connecting our autotransformer (see data sheet on www.victronenergy.com) to a 'European' inverter programmed to supply 240V / 60Hz.

PowerControl – Dealing with limited generator, shore-side or grid power

The Quattro is a very powerful battery charger. It will therefore draw a lot of current from the generator or shore side supply (Up to 40A per 5kVA Quattro at 120VAC). A current limit can be set on each AC input. The Quattro will then take account of other AC loads and use whatever is spare for charging, thus preventing the generator or shore supply from being overloaded.

PowerAssist - Boosting shore or generator power

This feature takes the principle of PowerControl to a further dimension allowing the Quattro to supplement the capacity of the alternative source. Where peak power is so often required only for a limited period, the Quattro will make sure that insufficient shore or generator power is immediately compensated for by power from the battery. When the load reduces, the spare power is used to recharge the battery.

Solar energy: AC power available even during a grid failure

The Quattro can be used in off grid as well as grid connected PV and other alternative energy systems.

System configuring has never been easier After installation, the Quattro is ready to go.

If settings have to be changed, this can be done in a matter of minutes with a new DIP switch setting procedure. Even parallel and 3-phase operation can be programmed with DIP switches: no computer needed!

Alternatively, VE.Net can be used instead of the DIP switches.

And sophisticated software (VE.Bus Quick Configure and VE.Bus System Configurator) is available to configure several new, advanced, features.







Quattro 24/5000/120-100/100



QUATTRO INVERTER/CHARGER 3KVA AND 5KVA 120V

Quattro	12/5000/200-100/100 120V	24/5000/120-100/100 120V	48/3000/35-50/50 120V	48/5000/70-100/100 120V			
PowerControl / PowerAssist		Yes					
Integrated Transfer switch		Yes					
AC inputs (2x)	Inp	ut voltage range: 90-140 VAC Input fre	equency: 45 – 65 Hz Power factor:	1			
Maximum feed through current (A)	2x100	2x100	2x50	2x100			
		INVERTER					
Input voltage range (V DC)	9,5 - 17	19 – 33	37,2 - 64,4	37,2 - 64,4			
Output (1)		Output voltage: 120 VAC \pm 2%	Frequency: 60 Hz \pm 0,1%				
Cont. output power at 25 °C (VA) (3)	5000	5000	3000	5000			
Cont. output power at 25 °C (W)	4500	4500	2500	4500			
Cont. output power at 40 °C (W)	4000	4000	2200	4000			
Peak power (W)	10000	10000	6000	10000			
Maximum efficiency (%)	94	94	94	95			
Zero-load power (W)	25	25	15	25			
Zero load power in AES mode (W)	20	20	10	20			
Zero load power in Search mode (W)	5	5	5	6			
		CHARGER					
Charge voltage 'absorption' (V DC)	14,4	28,8	57,6	57,6			
Charge voltage 'float' (V DC)	13,8	27,6	55,2	55,2			
Storage mode (V DC)	13,2	26,4	52,8	52,8			
Charge current house battery (A) (4)	200	120	35	70			
Charge current starter battery (A)	4	4	n.a.	n. a.			
Battery temperature sensor		Yes					
		GENERAL					
Auxiliary output (A) (5)	50	50	32	50			
Programmable relay (6)	3x	3x	3x	3x			
Protection (2)		a-g					
VE.Bus communication port	For p	arallel and three phase operation, remo	te monitoring and system integrati	on			
Remote on-off		res, 2x Ves					
Common Characteristics	Oper	res	dumidity (non condensing); max 95	5%			
common characteristics	oper	ENCLOSURE	furniarty (non condensing). maxi se	,,,,			
Common Characteristics	Ν	Material & Colour: aluminium (blue BAL)	5012) Protection category: IP 21				
Battery-connection		Four M8 holts (2 plus and 2	minus connections)				
buttery connection			Screw terminals 13 mm ² (6				
230 V AC-connection	M6 bolts	M6 bolts	AWG)	M6 bolts			
Weight (kg)	75 lb 34 kg	66 lb 30 kg	42 lb 19 kg	66 lb 30 kg			
Dimensions (hxwxd)	18,5 x 14,0 x 11,2 inch	17,5 x 13,0 x 9,6 inch	14.3x10.2x8.6 inch	17,5 x 13,0 x 9,6 inch			
	470 x 330 x 280 11111	STANDARDS	3028238821811111	444 x 328 x 240 mm			
Safety		EN 60335-1 EN	60335-2-29				
Emission Immunity		EN 500555 1, EN	4-2. FN 61000-3-3				
1) Can be adjusted to 50 Hz 2) Protection key: a) output short circuit b) overload c) battery voltage too high d) battery voltage too low e) temperature too high f) 120 VAC on inverter output g) input voltage ripple too high	 3) Non linear load, crest factor 3:1 4) At 25 °C ambient5) Switches off when no external AC source available 5) Switches off when no external AC source available 6) Programmable relay that can be set for general alarm, DC undervoltage or genset start/stop function AC rating: 120V/4A DC rating: 4A up to 35VDC, 1A up to 60VDC 7) A. o. to communicate with a Lithium Ion battery BMS 						
				and the second se			



Digital Multi Control

A convenient and low cost solution for remote monitoring, with a rotary knob to set Power Control and Power Assist levels.



Blue Power Panel Connects to a Multi or Quattro and all VE.Net devices, in particular the VE.Net Battery Controller. Graphic display of currents and voltages.



Computer controlled operation and monitoring Several interfaces are available:

- MK2.2 VE.Bus to RS232 converter
- Connects to the RS232 port of a computer (see 'A guide to VEConfigure')
- MK2-USB VE.Bus to USB converter Connects to a USB port (see 'A guide to VEConfigure')
- VE.Net to VE.Bus converter
- Interface to VE.Net (see VE.Net documentation)
- VE.Bus to NMEA 2000 converter
- Victron Global Remote

The Global Remote is a modem which sends alarms, warnings and system status reports to cellular phones via text messages (SMS). It can also log data from Victron Battery Monitors, Multi's, Quattro's and Inverters to a website through a GPRS connection. Access to this website is free of charge.

- Victron Ethernet Remote
- To connect to Ethernet.

080

BMV Battery Monitor

The BMV Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current. Besides this, the software includes complex calculation algorithms, like Peukert's formula, to exactly determine the state of charge of the battery. The BMV selectively displays battery voltage, current, consumed Ah or time to go. The monitor also stores a host of data regarding performance and use of the battery.



BLUE POWER BATTERY CHARGER IP20



Blue Power Battery Charger IP 20 12/15 (1)



Blue Power Battery Charger IP 20 24/15 (3)

Adaptive 4-stage charge characteristic: bulk – absorption – float – storage

The Blue Power charger features a microprocessor controlled 'adaptive' battery management. The 'adaptive' feature will automatically optimise the charging process relative to the way the battery is being used.

Less maintenance and aging when the battery is not in use: the Storage Mode

The storage mode kicks in whenever the battery has not been subjected to discharge during 24 hours. In the storage mode float voltage is reduced to 2,2 V/cell (13,2 V for a 12 V battery) to minimise gassing and corrosion of the positive plates. Once a week the voltage is raised back to the absorption level to 'equalize' the battery. This feature prevents stratification of the electrolyte and sulphation, a major cause of early battery failure.

Protected against overheating and silent fan cooling

Output current will reduce as temperature increases up to 60°C, but the Blue Power charger will not fail. The load and temperature controlled fan is practically inaudible

Two LED's for status indication

Yellow LED: bulk charge (blinking fast), absorption (blinking slow), float (solid) Green LED: power on

Learn more about batteries and battery charging

To learn more about batteries and charging batteries, please refer to our book 'Energy Unlimited' (available free of charge from Victron Energy and downloadable from <u>www.victronenergy.com</u>).

Blue Power Charger IP 20	12/7 (1) 12/10 (1) 12/15 (1)	12/25 (1) 12/25 (3)	24/5 (1) 24/8 (1)	24/15 (1) 24/15 (3)	
Input voltage range	90-265 VAC or 125-350 VDC	180-265 VAC or 250-350 VDC	90-265 VAC or 125-350 VDC	180-265 VAC or 250-350 VDC	
Frequency		45-65 Hz	z or DC		
Number of outputs	1	1 or 3	1	1 or 3	
Charge voltage 'absorption' (V DC)	14,4	14,4	28,8	28,8	
Charge voltage 'float' (V DC)	14	14	28	28	
Charge voltage 'storage' (V DC)	13,2	13,2	26,4	26,4	
Charge current (A)	7/10/15	25	5 / 8	15	
Charge characteristic	4-stage adaptive				
Minimum battery capacity (Ah)	24 / 30 / 45	75	16 / 24	45	
Can be used as power supply	Yes				
Protection	Batte	ery reverse polarity (fuse) Outp	out short circuit Over tempera	ture	
Operating temp. range		-20 to +60°C (full rated	d output up to 40°C)		
Humidity (non condensing)		Max 9	95 %		
		ENCLOSURE			
Material & Colour		Aluminium (bl	ue RAL 5012)		
Battery-connection	Black and red cable of 1,5 meter	Screw terminals 6 mm²	Black and red cable of 1,5 meter	Screw terminals 6 mm ²	
230 V AC-connection		Cable of 1,5 meter with CEE	7/7 or AS/NZS 3112 plug		
Protection category		IP 2	20		
Weight (kg)	1,3	1,3	1,3	1,3	
Dimensions (h x w x d in mm)	60 x 90 x 210	66 x 90 x 235	60 x 90 x 210	66 x 90 x 235	
		STANDARDS			
Safety		EN 60335-1, EN	N 60335-2-29		
Emission	EN 55014-1, EN 61000-6-3, EN 61000-3-2				
Immunity	EN 55014-2, EN 61000-6-1, EN 61000-6-2, EN 61000-3-3				



BLUE POWER BATTERY CHARGER IP20 180 VAC - 265 VAC

The highest efficiency ever!

Setting a new industry standard: with 93% efficiency or better, these chargers waste three to four times less heat.

And once the battery is fully charged, power consumption reduces to less than a Watt, some five to ten times better than the industry standard.

Adaptive 4-stage charge algorithm: bulk - absorption - float - storage

The Blue Power charger features a microprocessor controlled 'adaptive' battery management. The 'adaptive' feature will automatically optimise the charging process relative to the way the battery is being used.

Less maintenance and aging when the battery is not in use: the Storage Mode

The storage mode kicks in whenever the battery has not been subjected to discharge during 24 hours. In the storage mode float voltage is reduced to 2,2 V/cell (13,2 V for a 12 V battery) to minimise gassing and corrosion of the positive plates. Once a week the voltage is raised back to the absorption level to 'equalize' the battery. This feature prevents stratification of the electrolyte and sulphation, a major cause of early battery failure.

Totally silent

Models up to 12/15 and 24/8: no fan. Models 12/25 and 24/12: small inaudible low rpm fan, temperature controlled.

Protected against overheating

Output current will reduce as temperature increases up to 60°C, but the Blue Power charger will not fail.

Two LED's for status indication

Yellow LED: bulk charge (blinking fast), absorption (blinking slow), float (solid), storage (off) Green LED: power on

Learn more about batteries and battery charging

To learn more about batteries and charging batteries, please refer to our book 'Energy Unlimited' (available free of charge from Victron Energy and downloadable from <u>www.victronenergy.com</u>).

Blue Power Charger IP 20	12/7 (1) 12/10 (1) 12/15 (1)	12/25 (1)	24/5 (1) 24/8 (1)	24/12 (1)	
Input voltage range		180-265 VAC o	or 250-350 VDC		
Efficiency	94%	92%	95%	93%	
No load power consumption	0.5W	0.5W	0.5W	0.5W	
Frequency		45-65 H	lz or DC		
Number of outputs	1	1	1	1	
Charge voltage 'absorption' (V DC)	14,4	14,4	28,8	28,8	
Charge voltage 'float' (V DC)	13.8	13.8	27.6	27.6	
Charge voltage 'storage' (V DC)	13,2	13,2	26,4	26,4	
Charge current (A)	7/10/15	25	5 / 8	12	
Charge characteristic	4-stage adaptive				
Minimum battery capacity (Ah)	24 / 30 / 45	75	16 / 24	45	
Can be used as power supply	Yes				
Protection	Battery reverse polarity (fuse) Output short circuit Over temperature				
Operating temp. range		-20 to +60°C (full rate	ed output up to 40°C)		
Humidity (non condensing)		Max	95 %		
		ENCLOSURE			
Material & Colour		Aluminium (l	blue RAL 5012)		
Battery-connection	Black and red cable of 1,5 meter with battery clamps	Black and red cable of 1 meter	Black and red cable of 1,5 meter with battery clamps	Black and red cable of 1,5 meter	
230 V AC-connection	Cable of 1,5	meter with CEE 7/7 plug, BS 1	363 plug (UK) or AS/NZS 3112 plug	(AU/NZ)	
Protection category		IF	P 20		
Weight (kg)			1,3		
Dimensions (h x w x d in mm)		66 x 9	90 x 235		
		STANDARDS			
Safety		EN 60335-1,	EN 60335-2-29		
Emission		EN 55014-1, EN 610	000-6-3, EN 61000-3-2		
Immunity	EN 55014-2, EN 61000-6-1, EN 61000-6-2, EN 61000-3-3				



Blue Power Battery Charger IP 20 12/15



BLUE POWER BATTERY CHARGER WATERPROOF IP65



Blue Power Charger 24V 3A IP65

Completely encapsulated: waterproof, shockproof and ignition protected

Water, oil or dirt will not damage the Blue Power charger. The casing is made of cast aluminium and the electronics are moulded in resin.

Protected against overheating

Can be used in a hot environment such as a machine room. Output current will reduce as temperature increases up to 60°C, but the Blue Power charger will not fail.

Automatic three stage charging

Once the absorption voltage has been reached, the Blue Power charger will switch to float charge 2 hours after the charge current has reduced to a low break point current (see specifications), or after a 20 hour absorption period. The battery is therefore effectively protected against overcharging and can remain permanently connected to the charger. The charger will automatically reset and start a new charge cycle after interruption of the AC supply or after reduction of the output voltage to 12V resp. 24V due to a DC load.

Two LED's for status indication

Yellow LED: battery being charged Yellow LED and Green LED: absorption charge Green LED: float charge, the battery is charged

Learn more about batteries and battery charging

To learn more about batteries and charging batteries, please refer to our book 'Energy Unlimited' (available free of charge from Victron Energy and downloadable from <u>www.victronenergy.com</u>).

Blue Power charger Waterproof	12/7	12/17	24/3	24/12	
Input voltage range (V AC)	200-265				
Frequency (Hz)		45-	65		
Charge voltage 'absorption' (V DC)	14,4	14,4	28,8	28,8	
Charge voltage 'float' (V DC)	13,7	13,7	27,4	27,4	
Charge current (A)	7	17	3	12	
Charge characteristic		3 stage with max. 18 h	ours absorption time		
Minimum battery capacity (Ah)	15	35	6	24	
Breakpoint current (A)	0,7	1,7	0,3	1,2	
Can be used as power supply	\checkmark	\checkmark	\checkmark	\checkmark	
Protection (1)		a,b	,C,		
Operating temp. range	-20 to +60°C (full rated output up to 40°C)				
Humidity		Up to	100 %		
	ENCL	OSURE			
Material & Colour		aluminium (bl	ue RAL 5012)		
Battery-connection		Black and red ca	ble of 1,5 meter		
230 V AC-connection (2)	Cabl	le of 1,5 meter with CE	E 7/7 or AS/NZS 3112	olug	
Protection category		IP	65		
Weight (kg)	1,1	1,4	1,1	1,4	
Dimensions (h x w x d in mm)	43 x 80 x 155	47 x 99 x 193	43 x 80 x 155	47 x 99 x 193	
	STAN	DARDS			
Safety		EN 60335-1, E	N 60335-2-29		
Emission Immunity		EN 55014-1, EN 6100	0-6-3, EN 61000-3-2		
Automotive Directive	EN 55	5014-2, EN 61000-6-1, E	N 61000-6-2, EN 6100	0-3-3	
1) Protection key: a) Battery reverse polarity (fuse in battery cable) b) Output short circuit c) Over temperature	2) Other plug types on r	request			



Blue Power Charger 24V 12A IP65







CENTAUR CHARGER 12/24V



Centaur Battery Charger 24 30

Quality without compromise

Aluminium epoxy powder coated cases with drip shield and stainless steel fixings withstand the rigors of an adverse environment: heat, humidity and salt air.

Circuit boards are protected with an acrylic coating for maximum corrosion resistance.

Temperature sensors ensure that power components will always operate within specified limits, if needed by automatic reduction of output current under extreme environmental conditions.

Universal 90-265V AC input voltage range and also suitable for DC supply (AC-DC and DC-DC operation)

All models will operate without any adjustment needed over a 90 to 265 Volt input voltage range, whether 50 Hz or 60 Hz.

The chargers also accept a 90-400V DC supply.

Three outputs that each can supply the full output current

Three isolated outputs to simultaneously charge 3 battery banks Each output is capable to supply the full rated current.

Three stage charging, with temperature compensation

The Centaur charges at bulk rate until the output has reduced to 70 % of the rated Amps, at which a 4 hour timer begins. After the timed period the charger switches to float rate. An internal temperature sensor is used to compensate the charge voltage with – 2 mV/°C (– 1 mV/°F) per cell. A dip switch is available to select the optimum charge/float voltages for Flooded Lead-acid, Gel or AGM batteries.

Learn more about batteries and battery charging

To learn more about batteries and charging batteries (including the pro's and con's of multi bank charging and intelligent charging), please refer to our book 'Electricity on Board' (available free of charge from Victron Energy and downloadable from www.victronenergy.com).






CENTAUR CHARGER 12/24V

Centaur Charger	12/20	12/30 24/16	12/40	12/50	12/60 24/30	12/80 24/40	12/100 24/60	24/80	12/200 24/100
Input voltage (V AC)					90 – 265				
Input voltage (V DC)					90 - 400				
Input frequency (Hz)					45 – 65				
Power factor					1				
Charge voltage 'absorption' (V DC)					14,3 / 28,5 (1)				
(V DC)					13,5 / 27,0 (1)				
Output banks					3				
Charge current (A) (2)	20	30 / 16	40	50	60 / 30	80 / 40	100 / 60	80	200 / 100
Total output ammeter		Yes							
Charge characteristic	IUoU (Three stage charging)								
Recommended battery capacity (Ah)	80 - 200	120 - 300 45 - 150	160 - 400	200 - 500	240 - 600 120 - 300	320 - 800 160 - 400	400 - 1000 240 - 600	320 - 800	800 - 2000 400 - 1000
Temperature sensor		Internal, - 2mV / °C (- 1mV / °F) per cell							
Forced cooling				Yes, tempera	ture and current o	ontrolled fan			
Protection				Output she	ort circuit, over te	mperature			
Operating temp. range				- 2	0 to 60°C (0 - 140	°F)			
Ignition protected					Yes				
Humidity (non condensing)					max 95%				
				ENCLOSURE					
Material & Colour				alum	iinium (blue RAL 5	5012)			
Battery-connection	M6 studs	M6 studs	M8 studs	M8 studs	M8 studs	M8 studs	M8 studs	M8 studs	M8 studs
AC-connection				screw	-clamp 4 mm ² (A)	NG 6)			
Protection category					IP 21				
Weight kg (lbs)	3,8 (8.4)	3,8 (8.4)	5 (11)	5 (11)	5 (11)	12 (26)	12 (26)	16 (35)	16 (35)
Dimensions hxwxd in mm (hxwxd in inches)	355x215x110 (14.0x8.5x4.3)	355x215x110 (14.0x8.5x4.3)	426x239x135 (16.8x9.4x5.3)	426x239x135 (16.8x9.4x5.3)	426x239x135 (16.8x9.4x5.3)	505x255x130 (19.9x10.0x5.2)	505x255x130 (19.9x10.0x5.2)	505x255x230 (19.9x10.0x9.1)	505x255x230 (19.9x10.0x9.1)
				STANDARDS					
Safety				EN 60335	-1, EN 60335-2-29), UL 1236			
Emission Immunity	EN 55014-1. EN 61000-3-2								

Automotive Directive

EN 55014-2, EN 61000-3-3

Standard setting. Optimum charge/float voltages for Flooded Lead-acid, Gel-Cell or AGM batteries selectable by dip switch.

2) Up to 40 °C (100 °F) ambient. Output will reduce to approximately 80 % of nominal at 50 °C (120 °F) and 60 % of nominal at 60 °C (140°F).



BMV-600S Battery Monitor

The BMV- 600S Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current. Besides this, the software includes complex calculation algorithms, like Peukert's formula, to exactly determine the state of charge of the battery. The BMV – 600S selectively displays battery voltage, current, consumed Ah or time to go.

Battery Alarm An excessively high or low battery voltage is indicated by an audible and visual alarm.

Installation made easy

- Fasten the separate mounting plate (A) to the wall where you want to place the battery charger, and simply hook up the Centaur.
 Secure the bottom of the backside
- Secure the bottom of the backside (B) to the wall.





PHOENIX BATTERY CHARGER 12/24V



Phoenix charger 12V 30A



Phoenix charger 24V 25A

Adaptive 4-stage charge characteristic: bulk - absorption - float - storage

The Phoenix charger features a microprocessor controlled 'adaptive' battery management system that can be preset to suit different types of batteries. The 'adaptive' feature will automatically optimise the process relative to the way the battery is being used.

The right amount of charge: variable absorption time

When only shallow discharges occur (a yacht connected to shore power for example) the absorption time is kept short in order to prevent overcharging of the battery. After a deep discharge the absorption time is automatically increased to make sure that the battery is completely recharged.

Preventing damage due to excessive gassing: the BatterySafe mode (see fig. 2 below)

If, in order to quickly charge a battery, a high charge current in combination with a high absorption voltage has been chosen, the Phoenix charger will prevent damage due to excessive gassing by automatically limiting the rate of voltage increase once the gassing voltage has been reached (see the charge curve between 14,4 V and 15,0 V in fig. 2 below).

Less maintenance and aging when the battery is not in use: the Storage mode (see fig. 1 & 2 below)

The storage mode kicks in whenever the battery has not been subjected to discharge during 24 hours. In the storage mode float voltage is reduced to 2,2 V/cell (13,2 V for 12 V battery) to minimise gassing and corrosion of the positive plates. Once a week the voltage is raised back to the absorption level to 'equalize' the battery. This feature prevents stratification of the electrolyte and sulphation, a major cause of early battery failure.

To increase battery life: temperature compensation

Every Phoenix charger comes with a battery temperature sensor. When connected, charge voltage will automatically decrease with increasing battery temperature. This feature is especially recommended for sealed batteries and/or when important fluctuations of battery temperature are expected.

Battery voltage sense

In order to compensate for voltage loss due to cable resistance, Phoenix chargers are provided with a voltage sense facility so that the battery always receives the correct charge voltage.

Universal 90-265V AC input voltage range and also suitable for DC supply (AC-DC and DC-DC operation) The chargers will accept a 90-400V DC supply.

Computer interface

Every Phoenix Charger is ready to communicate with a computer through its RS-485 data port. Together with our VEConfigure software, which can be downloaded free of charge from our <u>website www.victronenergy.com</u> and the data link MK1b (see accessories), all parameters of the chargers can be customised.

Learn more about batteries and battery charging

To learn more about batteries and charging batteries, please refer to our book 'Energy Unlimited' (available free of charge from Victron Energy and downloadable from <u>www.victronenergy.com</u>). For more information about adaptive charging please look under Technical Information on our website.



Charge curves: up to the gassing voltage (fig.1), and exceeding the gassing voltage (fig.2)



PHOENIX BATTERY CHARGER 12/24V

Phoenix Charger	12/30	12/50	24/16	24/25		
Input voltage range (V AC)		90-	-265			
Input voltage range (V DC)		90-	-400			
Frequency (Hz)		45	i-65			
Power factor			1			
Charge voltage 'absorption' (V DC)	14,4	14,4	28,8	28,8		
Charge voltage 'float' (V DC)	13,8	13,8	27,6	27,6		
Storage mode (V DC)	13,2	13,2	26,4	26,4		
Charge current house batt. (A) (2)	30	50	16	25		
Charge current starter batt. (A)	4	4	4	4		
Charge characteristic		4 stage	adaptive			
Battery capacity (Ah)	100-400	200-800	100-200	100-400		
Temperature sensor	\checkmark	\checkmark	\checkmark	\checkmark		
Can be used as power supply	\checkmark	\checkmark	\checkmark	\checkmark		
Forced cooling	\checkmark	\checkmark	\checkmark	\checkmark		
Protection (1)		a,b,c,d				
Operating temp. range		-20 to 60°C (0 - 140°F)				
Humidity (non condensing)		max	\$ 95%			
		ENCLOSURE				
Material & Colour		aluminium (b	blue RAL 5012)			
Battery-connection		M6	studs			
AC-connection		screw-clamp 4	mm² (AWG 11)			
Protection category		IP	21			
Weight kg (lbs)		3,8	(8)			
Dimensions (hxwxd in mm and inches)		350x200x108 mm	(13.8x7.9x4.3 inch)			
		STANDARDS				
Safety		EN 60335-1, E	EN 60335-2-29			
Emission Immunity	EN 55014-1, EN 61000-3-2,					
Automotive Directive		EN 55014-2, EN 61000-3-3				
Vibration		IEC68-2-6:10	0-150Hz/1.0G			
1) Protection key:	2) Up to 40 °C (100 °F) ambient					

b) Battery reverse polarity detection



Battery Alarm

An excessively high or low battery voltage is indicated by an audible and visual alarm, and potential free contacts.





Phoenix Charger Control The PCC panel provides remote control and monitoring of the charge process with LED indication of the charger status. In addition, the remote panel also offers output current adjustment that can be used to limit the output current and thus the power drawn from the AC supply. This is particularly useful when operating the charger from limited shore power or small gensets. The panel can also be used to change the battery charging parameters.

The brightness of the LED's is automatically reduced during night time. Connection to the charger is with a standard UTP - cable.



BMV 600S Battery Monitor The BMV 600S Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current. Besides this, the software includes complex calculation algorithms, like Peukert's formula, to exactly determine the state of charge of the battery. The BMV 600S selectively displays battery voltage, current, consumed Ah or time to go.



SKYLLA-I BATTERY CHARGER 24V

Li-lon ready



Skylla-i 24/100 (3)

Skylla-i (1+1): two outputs to charge 2 battery banks

The Skylla-i (1+1) features 2 isolated outputs. The second output, limited to approximately 4 A and with a slightly lower output voltage, is intended to top up a starter battery.

Skylla-i (3): three full current outputs to charge 3 battery banks

The Skylla-i (3) features 3 isolated outputs. All outputs can supply the full rated output current.

Rugged

Aluminium epoxy powder coated cases with drip shield and stainless steel fixings withstand the rigors of an adverse environment: heat, humidity and salt air.

Circuit boards are protected with an acrylic coating for maximum corrosion resistance. Temperature sensors ensure that power components will always operate within specified limits, if needed by automatic reduction of output current under extreme environmental conditions.

Flexible

Next to a CAN bus (NMEA2000) interface, a rotary switch, DIP switches and potentiometers are available to adapt the charge algorithm to a particular battery and its conditions of use. Please refer to the manual for a complete overview of the possibilities

Important features:

The right amount of charge for a lead-acid battery: variable absorption time

When only shallow discharges occur the absorption time is kept short in order to prevent overcharging of the battery. After a deep discharge the absorption time is automatically increased to make sure that the battery is completely recharged.

Preventing damage due to excessive gassing: the BatterySafe mode

If, in order to quickly charge a battery, a high charge current in combination with a high absorption voltage has been chosen, the Skylla-i will prevent damage due to excessive gassing by automatically limiting the rate of voltage increase once the gassing voltage has been reached

Less maintenance and aging when the battery is not in use: the Storage mode

The storage mode kicks in whenever the battery has not been subjected to discharge during 24 hours. In the storage mode float voltage is reduced to 2,2 V/cell (26,4 V for 24 V battery) to minimise gassing and corrosion of the positive plates. Once a week the voltage is raised back to the absorption level to 'refresh' the battery. This feature prevents stratification of the electrolyte and sulphation, a major cause of early battery failure.

To increase battery life: temperature compensation

Every Skylla-i comes with a battery temperature sensor. When connected, charge voltage will automatically decrease with increasing battery temperature. This feature is especially recommended for sealed lead-acid batteries and/or when important fluctuations of battery temperature are expected.

Battery voltage sense

In order to compensate for voltage loss due to cable resistance, the Skylla-i is provided with a voltage sense facility so that the battery always receives the correct charge voltage.

Suitable for AC and DC supply (AC-DC and DC-DC operation) The chargers also accept a DC supply.

Use as a power supply

As a result of the perfectly stabilized output voltage, the Skylla-i can be used as a power supply if batteries or large buffer capacitors are not available.

Li-Ion (LiFePo4) ready

Simple charger on-off control can be implemented by connecting a relay or open collector optocoupler output from a Li-lon BMS to the remote control port of the charger. Alternatively complete control of voltage and current can be achieved by connecting to the galvanically isolated CAN bus port.

Learn more about batteries and battery charging

To learn more about batteries and charging batteries, please refer to our book 'Energy Unlimited' (available free of charge from Victron Energy and downloadable from <u>www.victronenergy.com</u>).



SKYLLA-I BATTERY CHARGER 24V

Skylla-i	24/80 (1+1)	24/80 (3)	24/100 (1+1)	24/100 (3)	
Input voltage (VAC)	230 V				
Input voltage range (VAC)		185-2	265 V		
Input voltage range (VDC)	180-350 V				
Maximum AC input current @ 180 VAC	16	δA	20	A	
Frequency (Hz)		45-6	5 Hz		
Power factor		0,9	98		
Charge voltage 'absorption' (VDC) (1)		28,	8 V		
Charge voltage 'float' (VDC)		27,	6 V		
Charge voltage 'storage' (VDC)		26,	4 V		
Charge current (A) (2)	80 A	3 x 80 A (max total output: 80A)	100 A	3 x 100 A (max total output: 100A)	
Charge current starter batt. (A)	4 A	n. a.	4	n. a.	
Charge characteristic		7 stage a	adaptive		
Battery capacity (Ah)	400-8	800 Ah	500-10	000 Ah	
Charge curve, Li-Ion	4 stage, with on-off control or Can bus control				
Temperature sensor	Yes				
Can be used as power supply	Yes				
Remote on-off port	Yes (can be connected to a Li-lon BMS)				
CAN bus communication port	Two RJ4	5 connectors, NMEA200	0 protocol, galvanically	isolated	
Remote alarm relay	DPST AC rat	ing: 240VAC/4A DC ra	ting: 4A up to 35VDC, 1	A up to 60VDC	
Forced cooling		Ye	es		
Protection	Battery reverse	polarity (fuse) Out	put short circuit Ov	er temperature	
Operating temp. range		-20 to 60°C (Full outp	ut current up to 40°C)		
Humidity (non condensing)		max	95%		
	ENCLC	SURE			
Material & Colour		aluminium (b	lue RAL 5012)		
Battery-connection		M8 k	oolts		
230 VAC-connection		screw-clamp 1	0mm² (AWG 7)		
Protection category		IP .	21		
Weight kg (lbs)		7 kg (16 lbs)		
Dimensions hxwxd in mm		405 x 250	x 150 mm		
(hxwxd in inches)	(16.0 x 9.9 x 5.9 inch)				
Safety	JIAND	EN 60335-1 E	N 60335-2-20		
Emission		EN 55014-1 EN 6100	0-6-3 EN 61000-3-2		
Immunity	ENI	55014-2 EN 61000-6-1 F	EN 61000-6-2 EN 61000	-3-3	
1) Output voltage range 20-36V.2) Up to 4Can be set with rotary switch orOutput	0°C (100°F) ambient. will reduce to 80% at 50°C	, and to 60% at 60°C.			





BMV 600S Battery Monitor

The BMV 600S Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current.

The software includes complex calculation algorithms, like Peukert's formula, to exactly determine the state of charge of the battery. The BMV 600S selectively displays battery voltage, battery current, consumed Ah or time to go.



Skylla-i Control

The Skylla-i Control panel provides remote control and monitoring of the charge process with LED status indication. In addition, the remote panel also offers input current adjustment that can be used to limit the input current and thus the power drawn from the AC supply. This is particularly useful when operating the charger from limited shore power or small gensets. The panel can also be used to change several battery charging parameters.



SKYLLA-TG CHARGER 24/48V 230V



Skylla TG 24 50



Skylla TG 24 50 3 phase



Charge voltage can be precisely adjusted to suit any sealed or unsealed battery system. In particular, sealed maintenance free batteries must be charged correctly in order to ensure a long service life. Overvoltage will result in excessive gassing and venting of a sealed battery. The battery will dry out and fail.

Suitable for AC and DC supply (AC-DC and DC-DC operation)

Except for the 3 phase input models, the chargers also accept a DC supply.

Controlled charging

Every TG charger has a microprocessor, which accurately controls the charging in three steps. The charging process takes place in accordance with the IUoUo characteristic and charges more rapidly than other processes.

Use of TG chargers as a power supply

As a result of the perfectly stabilized output voltage, a TG charger can be used as a power supply if batteries or large buffer capacitors are not available.

Two outputs to charge 2 battery banks (24V models only)

The TG chargers feature 2 isolated outputs. The second output, limited to approximately 4 A and with a slightly lower output voltage, is intended to top up a starter battery.

To increase battery life: temperature compensation

Every Skylla TG charger comes with a battery temperature sensor. When connected, charge voltage will automatically decrease with increasing battery temperature. This feature is especially recommended for sealed batteries which otherwise might be overcharged and dry out due to venting.

Battery voltage sense

In order to compensate for voltage loss due to cable resistance, TG chargers are provided with a voltage sense facility so that the battery always receives the correct charge voltage.

Learn more about batteries and battery charging

To learn more about batteries and charging batteries, please refer to our book 'Energy Unlimited' (available free of charge from Victron Energy and downloadable from <u>www.victronenergy.com</u>).



Skylla TG 24 100

Charge curve



Application example





SKYLLA-TG CHARGER 24/48V 230V

Skylla	24/30 TG	24/50 TG	24/80 TG	24/100 TG	24/100 TG	48/25 TG	48/50 TG
	24/50 IG	3 pnase			3 pnase		
Input voltage (V AC)	230	3 x 400	230	230	3 x 400	230	230
Input voltage range (V AC)	185-264	320-450	185-264	185-264	320-450	185-264	185-264
Input voltage range (V DC)	180-400	n. a.	180-400	180-400	n. a.	180-400	180-400
Frequency (Hz)				45-65			
Power factor				1			
Charge voltage 'absorption' (V DC)	28,5	28,5	28,5	28,5	28,5	57	57
Charge voltage 'float' (V DC)	26,5	26,5	26,5	26,5	26,5	53	53
Charge current house batt. (A) (2)	30 / 50	50	80	100	100	25	50
Charge current starter batt. (A)	4	4	4	4	4	n.a.	n.a.
Charge characteristic				IUoUo (three step)			
Battery capacity (Ah)	150-500	250-500	400-800	500-1000	500-1000	125-250	250-500
Temperature sensor		\checkmark					
Can be used as power supply		\checkmark					
Remote alarm	Potential free contacts 60V / 1A (1x NO and 1x NC)						
Forced cooling	\checkmark						
Protection (1)				a,b,c,d			
Operating temp. range			-	20 to 60°C (0 - 140°F)		
Humidity (non condensing)				max 95%			
			ENCLOSURE				
Material & Colour			alur	minium (blue RAL 50)12)		
Battery-connection				M8 studs			
230 V AC-connection			screw	/-clamp 2,5 mm ² (AV	VG 6)		
Protection category				IP 21			
Weight kg (lbs)	5,5 (12.1)	13 (28)	10 (22)	10 (22)	23 (48)	5,5 (12.1)	10 (12.1)
Dimensions hxwxd in mm	365x250x147	365x250x257	365x250x257	365x250x257	515x260x265	365x250x147	365x250x257
(hxwxd in inches)	(14.4x9.9x5.8)	(14.4x9.9x10.1)	(14.4x9.9x10.1)	(14.4x9.9x10.1)	(20x10.2x10.4)	(14.4x9.9x5.8)	(14.4x9.9x10.1)
Color.			STANDARDS	(0225 1 EN (0225 2	20		
Salety			ENG	50355-1, EN 60555-2	-29		
	EN 55014-1, EN 61000-5-2						
1) Protection			EN	55014-2, EN 61000	c-c		
 a. Output short circuit b. Battery reverse polarity detection 2) Up to 40°C (100°F) ambient 	c. Battery voltage too high d. Temperature too high						



BMV 600S Battery Monitor

The BMV 600S Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current. Besides this, the software includes complex calculation algorithms, like Peukert's formula, to exactly determine the state of charge of the battery. The BMV 600S selectively displays battery voltage, current, consumed Ah or time to go.



Skylla Control

The Skylla Control allows you to alter the charge current and see the system status. Altering the charge current is useful if the shore power fuse is limited: the AC current drawn by the battery charger can be controlled by limiting the maximum output current, thereby preventing the shore power fuse from blowing.



Charger Switch A remote on-off switch



Battery Alarm An excessively high or low battery voltage is indicated by an audible and visual alarm.

SKYLLA-TG CHARGER 24V 90-265V GL APPROVED



Skylla Charger 24V 50A

Universal 90-265V AC input voltage range and also suitable for DC supply

All models will operate without any adjustment needed over a 90 to 265 Volt input voltage range, whether 50 Hz or 60 Hz.

The chargers will also accept a 90-400V DC supply.

Germanischer Lloyd approval

The Chargers have been approved by Germanischer Lloyd (GL) to environmental category C, EMC 1. Category C applies to equipment protected from the weather. EMC 1 applies to conducted and radiated emission limits for equipment installed on the bridge of a ship.

The approval to GL C, EMC1 implies that the Chargers also complies to IEC 60945-2002, category "protected" and "equipment installed on the bridge of a ship".

The GL certification applies to 185-265V AC supply.

Other features

- Microprocessor control
- Can be used as power supply
- Battery temperature sensor for temperature compensated charging
- Battery voltage sensing to compensate for voltage loss due to cable resistance

Other Skylla chargers

- Standard 185-265V AC models with additional output to charge a starter battery
- GMDSS models, with all required monitoring and alarm functions.

Learn more about batteries and battery charging

To learn more about batteries and charging batteries, please refer to our book 'Energy Unlimited' (available free of charge from Victron Energy and downloadable from <u>www.victronenergy.com</u>).



Charge curve



SKYLLA-TG CHARGER 24V 90-265V GL APPROVED

Skylla-TG	24/30 90-265 VAC	24/50 90-265 VAC	24/100-G 90-265 VAC	
Input voltage (V AC)	230	230	230	
Input voltage range (V AC)	90-265	90-265	90-265	
Input voltage range (V DC)	90-400	90-400	90-400	
Frequency (Hz)		45-65 Hz or DC		
Power factor		1		
Charge voltage 'absorption' (V DC)	28,5	28,5	28,5	
Charge voltage 'float' (V DC)	26,5	26,5	26,5	
Charge current house batt. (A) (2)	30	50	100	
Charge current starter batt. (A)	4	4	4	
Charge characteristic	IUoUo (three step)			
Battery capacity (Ah)	150-300 250-500 500-1000			
Temperature sensor	\checkmark			
Can be used as power supply	\checkmark			
Remote alarm	Potential free contacts 60V / 1A (1x NO and 1x NC)			
Forced cooling	\checkmark			
Protection (1)	a,b,c,d			
Operating temp. range		-20 to 60°C (0 - 140°F)	l de la construcción de la constru	
Humidity (non condensing)		max 95%		
	ENCLOSU	RE		
Material & Colour		aluminium (blue RAL 50	12)	
Battery-connection		M8 studs		
230 V AC-connection		screw-clamp 2,5 mm ² (AW	/G 6)	
Protection category		IP 21		
Weight kg (lbs)	5,5 (12.1)	5,5 (12.1)	10 (22)	
Dimensions hxwxd in mm (hxwxd in inches)	365x250x147 (14.4x9.9x5.8)	365x250x147 (14.4x9.9x5.8)	365x250x257 (14.4x9.9x10.1)	
	STANDARI	OS		
Vibration	0,7g (IEC 60945)			
Safety	EN 60335-1, EN 60335-2-29, IEC 60945			
Emission		EN 55014-1, EN 61000-3-2, IE	C 60945	
Immunity	EN 55014-2, EN 61000-3-3, IEC 60945			

Immunity Germanischer Lloyd

Protection key:
 a) Output short circuit

b) Battery reverse polarity detection



BMV-600S Battery Monitor The BMV – 600 Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current. Besides this, the software includes complex calculation algorithms, like Peukert's formula, to exactly determine the state of charge of the battery. The BMV -600 selectively displays battery voltage, current, consumed Ah or time to go.

c) Battery voltage too high d) Temperature too high

Skylla Control

alter the charge current and see

the system status. Altering the

charge current is useful if the

charger can be controlled by

limiting the maximum output

current, thereby preventing the

shore power fuse from blowing.

shore power fuse is limited: the

AC current drawn by the battery



Charger Switch The Skylla Control allows you to



Battery Alarm An excessively high or low battery voltage is indicated by an audible and visual alarm.

A remote on-off switch

Certificate 54 758 – 08HH

2) Up to 40°C (100°F) ambient



SKYLLA-TG 24/30 AND 24/50 GMDSS



Skylla TG 24 30 GMDSS

GMDSS

The Global Maritime Distress & Safety System (GMDSS) was developed by the International Maritime Organisation (IMO) to improve maritime distress and safety communications.

Power supply

The Skylla TG has proven itself to be an excellent battery charger and power supply for GMDSS applications. However, when using a standard Skylla charger, additional equipment is needed to perform the monitoring and alarm functions required for GMDSS.

Installation made easy: the Skylla GMDSS

The Victron Skylla GMDSS charger has been designed to provide all required monitoring and alarm data. Both the battery and the GMDSS system are connected directly to the charger. Data and alarms are displayed on a digital panel (VE.Net GMDSS panel, to be ordered separately). A standard eight wire UTP cable connects the charger to the panel.

No adjustments needed

The whole system is 'click and go': the panels are pre-programmed for GMDSS functionality. A simple, intuitive menu allows changing of settings if required.

Battery time to go

The Skylla GMDSS charger has a built-in battery controller. The capacity of the battery is fully monitored so the panel can even indicate the 'time to go' in case of a power supply black out.

Perfect charger for any type of battery

Charge voltage can be precisely adjusted to suit any VRLA or flooded battery system.





SKYLLA-TG 24/30 AND 24/50 GMDSS

Skylla-TG	24/30 GMDSS	24/50 GMDSS			
Input voltage (V AC)	23)			
Input voltage range (V AC)	90 - 2	65			
Frequency (Hz)	45-6	55			
Power factor	1				
Charge voltage 'absorption' (V DC)	28,	5			
Charge voltage 'float' (V DC)	26,	5			
Charge current (A)	30	50			
Charge characteristic	IUoUo (thi	ee step)			
Temperature sensor	\checkmark				
Can be used as power supply	\checkmark				
Forced cooling	\checkmark				
Protection (1)	a,b,c	,d			
Operating temp. range	-20 to 60°C	(0 - 140°F)			
Humidity (non condensing)	max 95%				
ENCLOSURE					
Material & Colour	aluminium (blue RAL 5012)				
Battery-connection	Two 1,5 m cables				
GMDSS connection	One 1,5 r	n cable			
2201/ 10	Three wire 2,5 mm	² (AWG 6) cable			
230 V AC-connection	Length	: 2 m			
Protection category	IP 2	1			
Weight kg (lbs)	6 (1	3)			
Dimensions hxwxd in mm (bxwxd in inches)	485x25)x147 9x5 8)			
(nxwxd in incircs)	ACCESORIES	5,5,0)			
VE.Net GMDSS panel	To be ordered	l separately			
UTP cable	To be ordered	l separately			
	STANDARDS				
Safety	EN 60335-1, EN	60335-2-29			
Emission Immunity	EN 55014-1, E	N 61000-3-2			
Immunity	EN 55014-2, EN 61000-3-3				
Maritime Nav. & Radiocomm.	IEC 60	945			
1)Protection key: a) output short circuit b) Battery reverse polarity detection	c) Battery voltage too high d) Temperature too high	2) Up to 40°C (100°F) ambient			





Remote panel GMDSS The remote panel allows easy acces to all important data. Alarm settings are pre-set but can also be re-programmed.







ISOLATION TRANSFORMERS



Isolation Transformer 2000W



Isolation Transformer 3600W

Safety and prevention of galvanic corrosion

The isolation transformer eliminates any electrical continuity between AC shore power and the boat. It is essential for safety and eliminates the need for galvanic isolators and polarity alarms.

Safety is taken for granted in case of a normal on-shore installation. A fuse will blow or a GFCI (Ground Fault Current Interrupter) will trip in case of a short circuit or current leakage to ground. Connecting the ground wire of the shore-side supply to the metal parts of the boat will result in galvanic corrosion (see below). Bringing only the live and neutral wire on board results in an unsafe situation because GFCI's will not work nor will a fuse blow in case of a short circuit to a metal part on the boat.

Galvanic corrosion occurs when two dissimilar metals in electrical contact are simultaneously exposed to an electrically conducting fluid. Seawater and, to a lesser extent, fresh water are such fluids. In general, the more active alloy of the couple corrodes preferentially while the less active (more noble) material is cathodically protected. The rate of galvanic corrosion is a function of several variables including area ratios, conductivity of the fluid, temperature, nature of the materials, etc.

It is a misunderstanding that galvanic corrosion occurs only in metal and aluminium hulls. In fact it can occur on any boat as soon as a metallic part (the shaft and propeller) is in contact with water. Galvanic corrosion will quickly dissolve your sacrificial anodes, and attack the shaft, propeller and other metal parts in contact with water as soon as the boat is connected to the shore-side supply.

It might therefore be tempting not to connect the ground conductor: this is however extremely dangerous because GFCI's will not work nor will a fuse blow in case of a short circuit to a metal part on the boat.

The best solution to avoid galvanic corrosion and at the same time prevent any unsafe situation is to install an isolation transformer to connect to the shore-side supply.

The isolation transformer eliminates any electrical continuity between shore power and the boat. The shore power is fed to the primary side of the transformer and the ship is connected to the secondary. The isolation transformer completely isolates the boat from the shore ground. By connecting all metal parts to the neutral output on the secondary side of the transformer, a GFCI will trip or a fuse will blow in case of a short circuit.

Soft start is a standard feature of a Victron Energy isolation transformer. It will prevent the shore power fuse from blowing due to the inrush current of the transformer, which would otherwise occur.

It is also recommended, for optimal safety, to connect the secondary neutral of the transformer to ground when the boat is out of the water.

3600 Watt Auto 115/230V

This model will automatically switch to 115 V or 230 V supply, depending on input voltage. Supply 88 V – 130V: switches to 115 V supply Supply 185 – 250 V: switches to 230 V supply





ISOLATION TRANSFORMERS

Isolation Transformers	2000 Watt (1)	3600 Watt (1)	3600 Watt Auto 115/230V (1)	7000 Watt		
Input	115 or 230V	115 or 230V	115 / 230V Automatic 115/230V switching	230 V		
Output	115 or 230V	115 or 230V	115 or 230V	230 V		
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz		
Rating	17 / 8,5 A	32 / 16 A	32 / 16 A	32 A		
Soft start		Yes				
Transformer type		Toroidal (low noise, low weight)				
Input circuit breaker		ye	25			
		ENCLOSURE				
Common Characteristics	Ma	aterial: aluminium (blue RAL 5012)	Protection category: IP 2	1		
Weight	10 Kg	23 Kg	24 Kg	28 Kg		
Dimensions (h x w x d), mm	375x214x110		362 x 258 x 218			
		STANDARDS				
Safety		EN 60	0076			
1) Can be used as: 115 V to 115 V isolation transformer 115 V to 230 V isolation transformer	230 V to 230 V isolation transformer 230 V to 115 V isolation transformer					







ORION DC/DC CONVERTERS



Orion 24/12-5



Orion 24/12-17

Remote on-off connector on the high power models (see table below)

The remote on-off eliminates the need for a high current switch in the input wiring. The remote on-off can be operated with a low power switch or by the engine run/stop switch (see manual).

All models with adjustable output can also be used as a battery charger For example to charge a 12 Volt starter or accessory battery in an otherwise 24 V system.

All models with adjustable output can be paralleled to increase output current Up to five units can be connected in parallel.

The Orion 12/27,6-12: a 24 V battery charger (see page 2) To charge a 24 V battery from a 12 V system.

The output voltage of this model can be adjusted with a potentiometer

A super wide input range buck-boost regulator: the Orion 7-35/12-3 (see page 2) The Orion 7-35/12-3 is an isolated converter with a very wide input range, suitable for both 12 V and 24 V systems, and a fixed 12,6 V output.

Easy to install

Delivery includes four Insulated Fastons Female Crimp 6.3 mm (eight Fastons in case of the Orion 24/12-40).







Orion 24/12-70

Orion 24/12-25

Orion 24/12-40

NEW

Non isolated	Orion	Orion	Orion	Orion	Orion	Orion	Orion	Orion	Orion
converters	24/12-5	24/12-12	24/12-17	24/12-25	24/12-40	24/12-70	12/24-8	12/24-10	12/24-20
Input voltage range (V)	18-35	18-35	18-35	18-35	18-35	18-35	9-18	9-18	9-18
Undervoltage shutdown (V)	-	14	14	14	14	14	8	8	8
Undervoltage restart (V)	-	18	18	18	18	18	10	10	10
Output voltage adjustable with potentiometer	no	no	no	yes	no	yes	no	yes	yes
Output voltage (V)	12	12	12	Adjustable 10–15V F set 13,2V	12	Adjustable 10–15V Fset 13,2V	24	Adjustable 20-30V F set 26,4V	Adjustable 20-30V F set 26,4V
Efficiency (%)	92	95	94	96	95	92	95	95	93
Suitable to buffer-charge a battery	no	no	no	yes	no	yes	no	yes	yes
Can be connected in parallel	no	no	no	yes	no	yes	no	yes	yes
Continuous output current (A)	5	12	17	25	40	70	8	10	20
Max. Output current (A)	5	20	25	35	55	85	20	20	30
Fan assisted cooling (temp. controlled)	no	no	no	no	yes	yes	no	no	yes
Galvanic isolation	no	no	no	no	no	no	no	no	no
Off load current	< 5mA	< 7mA	< 7mA	< 15mA	< 20mA	< 20mA	< 10mA	< 15mA	< 30mA
Remote on-off	no	no	no	yes	yes	yes	no	no	yes
Operating temperature range (derate 3% per °C above 40°C)	-20 to +55°C	-20 to +55°C	-20 to +55°C	-20 to +55°C	-20 to +55°C	-20 to +55°C	-20 to +55°C	-20 to +55°C	-20 to +55°C
DC connection	Faston tabs 6.3 mm	Faston tabs 6.3 mm	Faston tabs 6.3 mm	Faston tabs 6.3 mm	Double Faston tabs 6.3 mm	M6 bolts	Faston tabs 6.3 mm	Faston tabs 6.3 mm	M6 bolts
Weight kg (lbs)	0,2 (0.40)	0,3 (0.65)	0,3 (0.65)	0,7 (1.55)	0,85 (1.9)	0,9 (2.0)	0,4 (0.8)	0,4 (0.9)	0,9 (2.0)
Dimensions hxwxd in mm (hxwxd in inches)	45x90x65 (1.8x3.5x2.6)	45x90x100 (1.8x3.5x3.9)	45x90x110 (1.8x3.5x3.9)	65x88x160 (2.6x3.5x6.3)	65x88x185 (2.6x3.5x7.3)	65x88x195 (2.6x3.5x7.7)	45x90x115 (1.8x3.5x4.5)	45x90x125 (1.8x3.5x4,5)	65x88x195 (2.6x3.5x7.7)

Notes:

- Other in- or output voltages at request

All natural convection cooled models can also be modified to IP65



ORION DC/DC CONVERTERS

Isolated converters	Orion xx/yy-100W	Orion xx/yy-200W	Orion xx/yy-360W
Power rating (W)	100 (12,5V/8A or 24V/4A)	200 (12,5V/16A or 24V/8A)	360 (12,5V/30A or 24V/15A)
Galvanic isolation	yes	yes	yes
Temperature increase after 30 minutes at full load (°C)	25	30	30
Fan assisted cooling (temp. controlled)	no	yes	yes
Weight kg (lbs)	0,5 (1.1)	0,6 (1.3)	1,4 (3.1)
Dimensions hxwxd in mm (hxwxd in inches)	49 x 88 x 152 (1.9 x 3.5 x 6.0)	49 x 88 x 182 (1.9 x 3.5 x 7.2)	64 x 163 x 160 (2.5 x 6.4 x 6.3)
Input voltage (xx): 12 V (9 – 18 V) or 24 V (20	– 35 V) or 48 V (30 – 60 V) or 96 V (60 – 120 V)	or 110V (60 – 140V)	

Output voltage (yy): 12,5 V, 24 V or 48V

Isolated 24V battery charger: Orion 12/27,6-12

Input 9 – 18 V, output 27,6 V, current limit 12 A, fan assisted cooling Output voltage adjustable with potentiometer Weight 1,4 kg (3.1 lbs), dimensions 64 x 163 x 160 mm (2.5 x 6.4 x 6.3 inch)

Isolated buck-boost regulator: Orion 7-35/12-3

Input 7 – 35 V, output 12,6 V current limit 3 A, derate current linearly from 3 A at 18 V to 1,5 A at 7 V Weight 1,4 kg (3.1 lbs), dimensions 64 x 163 x 160 mm (2.5 x 6.4 x 6.3 inch)

Common Characteristics			
Output voltage stability	2 % (Orion 12/24-7 and Orion 12/24-10: + 0% / - 5%)		
Output voltage tolerance	3 %		
Output noise	< 50 mV rms		
Off load current	< 25 mA (isolated converters)		
Efficiency	Non isolated: appr. 92% Isolated: appr. 85%		
Isolation	> 400 Vrms between input, output and case (isolated products only)		
Operating temperature	- 20 to + 30°C (0 to 90°F). Derate linearly to 0 A at 70°C (160°F)		
Humidity	Max 95% non condensing		
Casework	Anodised aluminum		
Connections	6.3 mm (2.5 inch) push-on flat blade connectors		
Protection: Overcurrent Overheating Reverse polarity conn. Overvoltage	Short circuit proof Reduction of output voltage Fuse and reverse connected diode across input Varistor (also protects against load dump)		
Standards: Emission	EN 50081-1		
Immunity Automotive Directive	EN 50082-1 95/45/EC		



Orion isolated 100W



Orion isolated 360W



BLUE POWER PANEL



Blue Power Panel GX



Blue Power Panel 2

Blue Power Panel

The Blue Power Panel provides intuitive control for all devices connected to the VE.Net network. It can be used to view and configure the full range of settings on VE.Net devices. Furthermore, its fully customizable overview screens make it the ideal monitoring tool for your power system.

The BPP now features an integrated VE.Net to VE.Bus Converter (VVC). This allows you to combine the powerful control of the VE Configure software with the simple interface of the BPP, without requiring a computer or additional interface devices.

BPP2 and BPP GX

The Blue Power Panel 2 and the Blue Power Panel GX almost have the same features. The difference between the two models is the design and the mounting of the panel. The body of the GX panel is made of plastic, which makes the panel lighter and adds a modern look to the panel. An extra advantage of the GX panel is the easy mounting: the included mounting frame allows the user to mount the panel from either front or back side. Due to the mounting frame, the mounting holes will no longer be in sight.

Features

- Full control & monitoring of all connected VE.Net devices
- Integrated VE.Net to VE.Bus Converter (VVC)
- Real-time system status read-outs
- Customizable overview screens
- Special mounting frame for front or back side mounting (only GX-model)
- Easy to install

	Blue Power Panel GX	Blue Power Panel 2		
Power supply voltage range	9 – 70	V DC		
	Current draw @ 12 V (VVC disabled)			
Standby	<1mA			
Backlight off	55r	nA		
Backlight on	70mA			
	Current draw @ 12 V (VVC enabled)			
Standby	<1mA			
Backlight off	70mA			
Backlight on	85r	nA		
Operating temp. range	-20	+50°C		
Potential free contact	3A/30VDC/250V A	C (Normally Open)		
	ENCLOSURE			
Material & Colour	plastic	aluminium		
Measurements front panel (w x h)	120 x 130 mm (Standard PROS2 Panel)			
Measurements body (w x h)	100 x 110 mm			
Weight	0.28	s Kg		





CYRIX-I 12/24V 120A AND 225A



Cyrix-i 12/24-120



Intelligent battery monitoring to prevent unwanted switching

Some battery combiners (also called voltage controlled relay, or split charge relay) will disconnect a battery in case of a short but high amperage load. A battery combiner also may fail to connect a large but discharged battery bank because the DC voltage immediately drops below the disengage value once the batteries are connected. The software of the Cyrix-i 12/24 does more than simply connect and disconnect based on battery voltage and with a fixed time delay. The Cyrix-i 12/24 looks at the general trend (voltage increasing or decreasing) and reverses a previous action only if the trend has reversed during a certain period of time. The time delay depends on the voltage deviation from the trend.

(for Battery Combiners with multiple engage/disengage profiles, please see the Cyrix-i 200A-400A)

12/24V auto ranging

The Cyrix-i 12/24 automatically detects system voltage.

No voltage loss

Cyrix battery combiners are an excellent replacement for diode isolators. The main feature is that there is virtually no voltage loss so that the output voltage of alternators or battery chargers does not need to be increased.

Prioritising the starter battery

In a typical setup the alternator is directly connected to the starter battery. The accessory battery, and possibly also a bow thruster and other batteries are each connected to the starter battery with Cyrix battery combiners. When a Cyrix senses that the starter battery has reached the connect voltage it will engage, to allow for parallel charging of the other batteries.

Bidirectional voltage sensing and power supply from both batteries

The Cyrix senses the voltage of both connected batteries. It will therefore also engage if for example the accessory battery is being charged by a battery charger.

The Cyrix-i 12/24 has a dual power supply. It will therefore also close if the voltage on one battery is too low to operate the Cyrix.

In order to prevent unexpected operation during installation or when one battery has been disconnected, the Cyrix-i 12/24 will not close if the voltage on one of the two battery connections is lower than 2V (12V battery) or 4V (24V battery).

Parallel connection in case of emergency (Start Assist)

The Cyrix can also be engaged with a push button (Cyrix remains engaged during 30 seconds) or a switch to connect batteries in parallel manually.

This is especially useful in case of emergency when the starter battery is discharged or damaged.

Cyrix battery combiner	Cyrix-i 12/24-120	Cyrix-i 12/24-225	
Continuous current	120 A	225 A	
Cranking rating (5 seconds)	180 A	500 A	
Connect voltage	From 13V to 13,8V and 26 to 27,6V with intelligent trend detection		
Disconnect voltage	From 11V to 12,8V and 22 to 25,7V with intelligent trend detection		
urrent consumption when open	<4 mA		
Start Assist	Yes (Cyrix remains engaged during 30 seconds)		
Protection category	IP54		
Weight kg (lbs)	0,11 (0.24)	0,66 (1.45)	
Dimensions h x w x d in mm	46 x 46 x 80	100x90x100	
(h x w x d in inches)	(1.8 x 1.8 x 3.2)	(4.0x3.5x4.0)	



Cyrix-i 12/24-225



CYRIX-I 200A-400A 12/24V AND 24/48V



Cyrix-i 24/48V 400A

New: intelligent battery monitoring to prevent unwanted switching

Some battery combiners will disconnect a battery in case of a short but high amperage load. A battery combiner also may fail to connect a large but discharged battery bank because the DC voltage immediately drops below the disengage value once the batteries are connected.

The software of the Cyrix-i does more than simply connect and disconnect based on battery voltage and with a fixed time delay. The Cyrix-i looks at the general trend (voltage increasing or decreasing) and reverses a previous action only if the trend has reversed during a certain period of time. The time delay depends on the voltage deviation from the trend.

In addition, four switch timing profiles can be chosen (see back page).

12/24V and 24/48V auto ranging

The Cyrix-i automatically detects system voltage.

No voltage loss

Cyrix battery combiners are an excellent replacement for diode isolators. The main feature is that there is virtually no voltage loss so that the output voltage of alternators or battery chargers does not need to be increased.

Prioritising the starter battery

In a typical setup the alternator is directly connected to the starter battery. The accessory battery, and possibly also a bow thruster and other batteries are each connected to the starter battery with Cyrix battery combiners. When a Cyrix senses that the starter battery has reached the connect voltage it will engage, to allow for parallel charging of the other batteries.

Bidirectional voltage sensing and power supply from both batteries

The Cyrix senses the voltage of both connected batteries. It will therefore also engage if for example the accessory battery is being charged by a battery charger.

The Cyrix-i has a dual power supply. It will therefore also close if the voltage on one battery is too low to operate the Cyrix.

In order to prevent unexpected operation during installation or when one battery has been disconnected, the Cyrix-i will not close if the voltage on one of the two battery connections is lower than 2V (12V battery), or 4V (24V battery) or 8V (48V battery).

Parallel connection in case of emergency

The Cyrix can also be engaged with a push button (Cyrix remains engaged during 30s) or a switch to connect batteries in parallel manually.

This is especially useful in case of emergency when the starter battery is discharged or damaged.

Model	Cyrix-i 12/24-200 Cyrix-i 24/48-200	Cyrix-i 12/24-400 Cyrix-i 24/48-400
Continuous current	200A	400A
Peak current	1000A during 1 second	2000A during 1 second
Input voltage 12/24V model	8-36VDC	8-36VDC
Input voltage 24/48V model	16-72VDC	16-72VDC
Connect/disconnect profiles	See table	See table
Over voltage disconnect	16V / 32 / 64V	16V / 32 / 64V
Current consumption when open	4 mA	4 mA
Emergency start	Yes, 30s	Yes, 30s
Micro switch for remote monitoring	Yes	Yes
Status indication	Bicolor LED	Bicolor LED
Weight kg (lbs)	0,9 (2.0)	0,9 (2.0)
Dimensions h x w x d in mm	78 x 102 x 110	78 x 102 x 110
(h x w x d in inches)	(3.1 x 4.0 x 4.4)	(3.1 x 4.0 x 4.4)



CYRIX-I 200A-400A 12/24V AND 24/48V

Profile 0					
Connect (V)*		Disconr	ect (V)*		
Less than13V	Remains open	More than 12,8V	Remains closed		
	Closes after		Opens after		
13V	10 min	12,8V	10 min		
13,2V	5 min	12,4V	5 min		
13,4V	3 min	12,2V	1 min		
13,6V	1 min	12V	4 sec		
13,8V	4 sec	Less than 11V	Immediate		

Profile 1				
Connect (V)*		Disconi	nect (V)*	
Less than 13,25V	Remains open	More than 12,75V	Remains closed	
More than 13,25V	Closes after 30 sec	From 10,5V to 12,75V	Opens after 2 min	
		Less than 10,5V	Immediate	

Profile 2				
Connect (V)*		Disconr	nect (V)*	
Less than13,2V	Remains open	More than 12,8V	Remains closed	
More than 13,2V	Closes after 6 sec	From 10,5V to 12,8V	Opens after 30 sec	
		Less than 10,5V	Immediate	

Profile 3					
Connect (V)*		Disconr	nect (V)*		
Less than13,25V	Remains open	More than 13,5V	Remains closed		
	Closes after		Opens after		
13V	10 min	12,8V	30 min		
13,2V	5 min	12,4V	12 min		
13,4V	3 min	12,2V	2 min		
13,6V	1 min	12V	1 min		
13,8V	4 sec	Less than 10,5V	Immediate		

NOTES

1) After connecting 3 times, the minimum time to reconnect is 1 minute (to prevent "rattling")

2) The Cyrix will not connect if the voltage on one of the battery connections is less than 2V*. (to prevent unexpected switching during installation)

3) The Cyrix will always connect if the start assist is activated, as long as the voltage on one of the battery connections is sufficient to operate the Cyrix (approximately 10V*).

* Multiply voltage x2 for 24V systems and x4 for 48V systems





VICTRON GLOBAL REMOTE 2 AND VICTRON ETHERNET REMOTE





Victron Global Remote 2



Victron Ethernet Remote

Victron Global Remote 2: A GSM/GPRS modem

The Global Remote is a modem which sends alarms, warnings and system status reports to cellular phones via text messages (SMS). It can also log data from Victron Battery Monitors, Multi's, Quattro's and Inverters to a website through a GPRS connection. The usage of this website is free of charge.

Victron Ethernet Remote: A GSM/GPRS modem with Ethernet connection

The Ethernet Remote has the same functions as the Global Remote. An extra function of the Ethernet Remote is that it can connect with LAN, due to a special cable. In this way, the Ethernet Remote can be connected to the internet without a SIM-card.

Simple and easy to use

The idea is simple: you can use it to get SMS alarms from a Multi, a Battery System, or both. When monitoring the usage of batteries, it can be extremely helpful to receive under and overvoltage alarms; whenever they occur. For this purpose, the Global Remote is perfect. A prepaid SIM-card (for example) in combination with the Global Remote is adequate for remotely monitoring your system.

Connections Global Remote

The Global Remote has two serial connections. The can be used to connect to a VE.Bus Multi/Quattro/Inverter unit or system. This connection needs a MK2 which is supplied with the VGR. The other connection is to connect a BMV-600S or BMV-602S Battery Monitor. To connect it to a BMV you will also need the connection kit accessory which needs to be purchased separately. The Global Remote also has a connection for an optional accessory, the VGR IO Extender.

Connections Ethernet Remote

The Ethernet Remote has one serial connection. This can be used to connect to a VE.Bus Multi/Quattro/Inverter unit or system, or a BMV Battery Monitor. To connect it to a BMV you will also need the connection kit accessory which needs to be purchased separately.

Advanced usage: Monitoring historic data

Taking it one step further, an internet browser and -connection is all you need to view all of the data online. You can simply create an account on the website and add your modem(s). Subsequently you can configure the GPRS connection, which will enable you to monitor the historic data of several basic properties such as system voltages, power levels and status information. All of this data is graphed. These graphs are available in daily, weekly and monthly timeframes.

Victron Remote Management

Victron Remote Management is the name of the system which consists of the VGR and the monitoring website. To get a preview: please go to https://vrm.victronenergy.com, and login with below details.

Username: demo@victronenergy.com Password: vrmdemo

Victron Global Remote







Battery Monitor

58

Ouattro

Battery Monitor



VICTRON GLOBAL REMOTE 2 AND VICTRON ETHERNET REMOTE

	Victron Global Remote 2	Victron Ethernet Remote			
Serial connection (Mk2.2a – included)	Connect VE.Bus Multi/Quattro/Inverter unit/system				
Serial connection (BMV-602 Datalink – not included)	Connect BMV-602	Battery Monitor			
	GENE	RAL			
Power supply voltage range	5.5 to 3	2VDC			
Current draw (max.)	0.48A at	5.5VDC			
Current draw (connected to GSM network)	90mA at 12VDC and	d 50mA at 24 VDC			
Operating temperature range	-30° to 75° C. /	-22° to 167° F.			
	ENCLC	SURE			
Dimensions VGR Modem (hxwxd)	73 x 54.5 x 25.5 mm	/ 2.9 x 2.1 x 1 inch			
Weight VGR Modem	89 grams / 3	3.1 ounces			
Body	Aluminium				
Installation	Two aluminum mounting bridles				
	GSM /	GPRS			
GPRS data usage	Depends on usage				
Antenna connection	50 Ohm SMA				
	INCLUDED A	CCESSORIES			
GSM antenna	Included	Included			
Ethernet attachment	n.a.	Included			
Battery cable	With inline fuse	Included			
Y-cable for serial and IO Extender connection	Included	Included			
Male DB15 to female DB9 cable	Included	Included			
MK2 interface	Included	Included			
	OPTIONAL ACCESSORIES (NOT INCLU	DED, TO BE ORDERED SEPARATELY)			
Global Remote to BMV-60xS conn. kit	Compatible	Compatible			
VGR IO Extender	Compatible	Not compatible			
Global Remote Antenna	Compatible	Compatible			



BMV-600S and 602S

The BMV-600S and 602S are our newest high precision battery monitors. The essential function of a battery monitor is to calculate ampere-hours consumed as well as the state of charge of a battery, Ampere-hours consumed are calculated by integrating the current flowing in or out of the battery.



Global Remote Antenna

The Global Remote Antenna is an optional accessory to improve the reception of the Victron Global Remote. The Global Remote Antenna replaces the standard antenna that is included with the Global Remote. The antenna is an outdoor 4dBi Gain antenna for stationary usage. A standard 5m low loss coax cable and wall-mount is included.

Specifications:

From		
rieu	uencv	

Connector:

Frequency:	900 (2dBi) / 1800 &
	1900-1990 and
	1990-2200 and
	2400Mhz
Vertically polarized	
Antenna length:	24cm

Antenna len Antenna diameter: 1,8cm Impedance: 50 Ω SMA-M connector



Victron Global Remote MultiPlus to BMV-60xS conn. kit Inverter/Charger Cable kit required to connect the BMV-60xS and the Victron

Global Remote. BMV 60xS

Data Link included.

The MultiPlus is a powerful true sine wave inverter, a sophisticated battery charger that features adaptive charge technology, and a high-speed AC transfer switch in a single compact enclosure.



Phoenix Inverter Pure sinwave output, high peak power and high efficiency. Combined high frequency and line frequency technologies ensure the best of both worlds.



Quattro Inverter/Charger

The Quattro can be connected to two independent AC sources, for example shoreside power and a generator, or two generators. The Quattro will automatically connect to the active source.

Example of graph available on https://vrm.victronenergy.com



Note that it is not possible to combine the Global Remote or Ethernet Remote with one of the following products in a VE.Bus system:

- VE.Net to VE.Bus Converter
- Blue Power Panel 2
- **Blue Power Panel GX**
- VE.Bus to NMEA2000 interface



PRECISION BATTERY MONITORING





BMV bezel square



BMV shunt 500A/50mV With quick connect pcb



BMV 602S Black



Precision monitoring

The essential function of a battery monitor is to calculate ampere-hours consumed and the state of charge of a battery. Ampere-hours consumed is calculated by integrating the current flowing in or out of the battery. In case of a constant current, this integration is equivalent to current multiplied by time. A discharge current of 10A during 2 hours, for example, amounts to 20Ah consumed. All our battery monitors are based on a powerful microprocessor, programmed with the algorithms needed for precision monitoring.

Standard information and alarms

- Battery voltage (V).
- Battery charge/discharge current (A).
- Ampere-hours consumed (Ah).
- State of charge (%).
- Time to go at the current rate of discharge.
- Visual and audible alarm: over- and under voltage, and/or battery discharged.
- Programmable alarm or generator start relay.
- BMV 600S: low cost ultra high resolution monitor
- Highest resolution: 10mA (0,01A) with 500A shunt.
- Can be used with 50, 60 or 100mV shunts, current rating from 100A to 1000A
- Lowest current consumption: 4mA @12V and 3mA @ 24V.
- Easiest to wire: the BMV 600S comes with shunt, 10 meter RJ 12 UTP cable and 2 meter battery cable with fuse: no other components needed.
- Easiest to install: separate front bezel for square or round appearance; ring for rear mounting and screws for front mounting.
- Broadest voltage range: 9.5 95 VDC without prescaler needed.
- Communication port (Isolated RS232 interface is needed to connect to a computer)

BMV 602S: two batteries

In addition to all the features of the BMV600S, the BMV602S can measure the voltage of a second battery. A version with a black front bezel (BMV 602S Black) is also available.

BMV 600HS: 70 to 350VDC voltage range

No prescaler needed. Note: suitable for systems with grounded minus only (battery monitor is not isolated from shunt).

Optional Isolated RS232 communication interface and software

(for all BMV models) Displays all information on a computer and loads charge/discharge data in an Excel file for graphical display. The BMV models feature a very simple protocol that can be used for integration into other systems.

VE.Net Battery Controller: any number of batteries

One VE.Net panel or Blue Power panel will connect to any number of battery controllers.
 Comes with 500A/50mV shunt and can be programmed for 50, 60 or 100mV shunts, current rating from 100A to 10.000A.

- With use, abuse and data memory.

- Temperature sensor and connection kit included.

High voltage VE.Net Battery Controller: 70 to 350VDC

No prescaler needed. Note: RJ45 connectors are galvanically isolated from Controller and shunt.



Example of a battery charge curve recorded with a BMV 602 and VEBat software



PRECISION BATTERY MONITORING

Battery monitor	BMV 600S	BMV 602S & BMV 602S BLACK	BMV 600HS	VE. Net Battery Controller	VE. Net High Voltage Battery Controller
Power supply voltage range	9.5 - 90 VDC	9.5 - 90 VDC	70 – 350 VDC	7 - 75 VDC	70 - 350 VDC ¹
Current draw, back light off	< 4 mA	< 4 mA	< 4 mA	< 5 mA	< 4 mA
Input voltage range (VDC)	9.5 - 95 VDC	9.5 - 95 VDC	70 – 350 VDC	0 - 75 VDC	0 – 350 VDC
Battery capacity (Ah)		20 - 9999 Ah		20 - 60	000 Ah
Operating temperature range			-20 +50°C (0-120°F)		
Measures voltage of second battery	No	Yes	Yes	Ν	lo
Communication port	Yes	Yes	Yes	Yes (V	/E.Net)
Potential free contacts			60V/1A (N/O)		
		RESOLUTION (with a 500	A shunt)		
Current		± 0,01 A		± 0,	,1 A
Voltage			± 0,01 V		
Amp hours	± 0,1 Ah				
State of charge (0 – 100 %)	± 0,1 %				
Time to go	± 1 min				
Temperature (0 - 50°C or 30 - 120°F)	n.a.				(± 1°F)
Accuracy of current measurement	± 0,3 %				
Accuracy of voltage measurement	± 0,4 %				
INSTALLATION & DIMENSIONS					
Installation	Flush mount DIN rail			rail	
Front		63 mm diameter		22 X 75 mm(0.9 x 2.9 inch)
Front bezel	(69 x 69 mm(2.7 x 2.7 inch)	1	n.	a.
Body diameter		52mm (2.0 inch)		n.	a.
Body depth		31mm (1.2 inch)		105 mm	(4,1 inch)
ACCESSORIES					
Shunt (included)	500 A / 50 mV ² 500 A / 50 mV ³				50 mV ³
Cables (included)	10 meter 6 core UTP with RJ12 connectors, Supplied with 1 m cables and cable with fuse for '+' connection Supplied with 1 m cables			h 1 m cables	
Temperature sensor	n. a. Supplied with 3 m cable			th 3 m cable	
Computer interface	optional n.a.				a.
	 7 – 75 VDC needed for VE. 	Net network power supply			

7 - 75 VDC needed for VE.Net network power supply
 2) HV version with shunt in plastic enclosure
 3) HV version with shunt + Controller in plastic enclosure



Victron Global Remote

The Global Remote is a modem which sends alarms, warnings and system status reports to cellular phones via text messages (SMS). It can also log data from Victron Battery Monitors, MultiPlus units, Quattro's and Inverters to a website through a GPRS connection. Access to this website is free of charge.



Victron Global Remote to BMV 60xS Connection Kit

Cable kit required to connect the BMV and the Victon Global Remote. BMV 60xS Data Link included.



Blue Power panel

The VE.Net Blue Power Panel is the panel that connects to the VE.Net Battery Controller. The panel can show the information of multiple batteries on one display for simple and efficient monitoring of your battery systems. For our other VE.Net products please refer to our VE.Net datasheet.



1000A/50mV shunt For ease of use with BMV series: quick connect pcb of standard 500A/50mV shunt can be mounted on this shunt.



2000A/50mV shunt For ease of use with BMV series: quick connect pcb of standard 500A/50mV shunt can be mounted on this shunt.



BMV-602 Data Link with software For all BMV's



ARGO DIODE BATTERY ISOLATORS



Argo Diode Isolator 120-2AC



Argo Diode Isolator 140-3AC

Diode battery isolators allow simultaneous charging of two or more batteries from one alternator, without connecting the batteries together. Discharging the accessory battery for example will not result in also discharging the starter battery.

The Argo battery isolators feature a low voltage drop thanks to the use of Schottky diodes: at low current the voltage drop is approximately 0,3 V and at the rated output approximately 0,45 V. All models are fitted with a compensation diode that can be used to slightly increase the output voltage of the alternator. This compensates for the voltage drop over the diodes in the isolator.

Please see our book 'Energy Unlimited' or ask for specialist advice when installing a diode isolator. Simply inserting the isolator in the cabling between the alternator and the batteries will slightly reduce charge voltage. The result can be that batteries are not charged to the full 100% and age prematurely.

Alternator energize input

Some alternators need DC voltage on the B+ output to start charging. Obviously, DC will be present when the alternator is directly connected to a battery. Inserting a Diode or FET splitter will however prevent any return voltage/current from the batteries to the B+, and the alternator will not start.

The new "AC" diode isolators feature a special current limited energize input that will power the B+ when the engine run/stop switch is closed.

Argo Diode Battery Isolator	80-2SC	80-2AC	100-3AC	120-2AC	140-3AC	160-2AC	180-3AC
Maximum charge current (A)	80	80	100	120	140	160	180
Maximum alternator current (A)	80	80	100	120	140	160	180
Number of batteries	2	2	3	2	3	2	3
Alternator Energize Input	no	yes	yes	yes	yes	yes	yes
Connection	M6 Studs	M6 Studs	M6 Studs	M8 Studs	M8 Studs	M8 Studs	M8 Studs
Compensation diode and	6,3 mm	6,3 mm	6,3 mm	6,3 mm	6,3 mm	6,3 mm	6,3 mm
Energize connection	Faston	Faston	Faston	Faston	Faston	Faston	Faston
Weight kg (lbs)	0,5 (1.3)	0,6 (1.3)	0,8 (1.8)	0,8 (1.8)	1,1 (2.5)	1,1 (2.5)	1,5 (3.3)
Dimensions h x w x d in mm (h x w x d in inches)	60 x 120 x 75 (2.4 x 4.7 x 3.0)	60 x 120 x 90 (2.4 x 4.7 x 3.9)	60 x 120 x 115 (2.4 x 4.7 x 4.5)	60 x 120 x 115 (2.4 x 4.7 x 4.5)	60 x 120 x 150 (2.4 x 4.7 x 5.9)	60 x 120 x 150 (2.4 x 4.7 x 5.9)	60 x 120 x 200 (2.4 x 4.7 x 7.9)





ARGO FET BATTERY ISOLATORS



Argo FET 100-3 3bat 100A



In contrast with diode battery isolators, FET isolators have virtually no voltage loss. Voltage drop is less than 0,02 Volt at low current and averages 0,1 Volt at higher currents.

When using ARGO FET Battery Isolators, there is no need to also increase the output voltage of the alternator. Care should taken however to keep cable lengths short and of sufficient cross section.

Example:

When a current of 100 A flows through a cable of 50 mm² cross section (AWG 0) and 10 m length (30 ft), the voltage drop over the cable will be 0,26 Volt. Similarly a current of 50 A through a cable of 10 mm² cross section (AWG 7) and 5 m length (15 ft) will result in a voltage drop of 0,35 Volt!

Alternator energize input

Some alternators need DC voltage on the B+ output to start charging. Obviously, DC will be present when the alternator is directly connected to a battery. Inserting a Diode or FET splitter will however prevent any return voltage/current from the batteries to the B+, and the alternator will not start. The new Argofet isolators have a special current limited energize input that will power the B+ when the engine run/stop switch is closed.

Argo FET Battery Isolator	Argofet 100-2	Argofet 100-3	Argofet 200-2	Argofet 200-3
Maximum charge current (A)	100	100	200	200
Maximum alternator current (A)	100	100	200	200
Number of batteries	2	3	2	3
Connection	M8 bolts	M8 bolts	M8 bolts	M8 bolts
Weight kg (lbs)	1,4 (3.1)	1,4 (3.1)	1,4 (3.1)	1,4 (3.1)
Dimensions h x w x d in mm (h x w x d in inches)	65 x 120 x 200 (2.6 x 4.7 x 7.9)	65 x 120 x 200 (2.6 x 4.7 x 7.9)	65 x 120 x 200 (2.6 x 4.7 x 7.9)	65 x 120 x 200 (2.6 x 4.7 x 7.9)





Argo FET 100-3 3bat 100A



BLUESOLAR CHARGE CONTROLLERS MPPT 70/15





Solar charge controller MPPT 70/15



Maximum Power Point Tracking

Upper curve:

Output current (I) of a solar panel as function of output voltage (V). The maximum power point (MPP) is the point Pmax along the curve where the product I x V reaches its peak.

Lower curve:

Output power $P = I \times V$ as function of output voltage.

When using a PWM (not MPPT) controller the output voltage of the solar panel will be nearly equal to the voltage of the battery, and will be lower than Vmp.

Ultra fast Maximum Power Point Tracking (MPPT)

Especially in case of a clouded sky, when light intensity is changing continuously, an ultra fast MPPT controller will improve energy harvest by up to 30% compared to PWM charge controllers and by up to 10% compared to slower MPPT controllers.

BatteryLife: intelligent battery management

When a solar charge controller is not able to recharge the battery to its full capacity within one day, the result is often that the battery will be continually be cycled between a "partially charged" state and the "end of discharge" state. This mode of operation (no regular full recharge) will destroy a lead-acid battery within weeks or months.

The BatteryLife algorithm will monitor the state of charge of the battery and day by day slightly increase the load disconnect level until absorption voltage is reached. From that point onwards the load disconnect level will be modulated so that absorption voltage is reached about once every week.

The MPPT 70/15 can also be set to follow the traditional load control mode with a fixed disconnect voltage

The load output is short circuit proof and can supply capacitive loads such as an inverter

Resin encapsulated electronics

Protects the electronic components against the environment

Automatic battery voltage recognition

The MPPT 70/15 will automatically adjust to a 12V or a 24V system.

BlueSolar charge controller	MPPT 70/15
Battery voltage	12/24 V Auto Select
Maximum battery current	15 A
Maximum PV power, 12V 1a,b)	200 W (MPPT range 15 V to 70 V)
Maximum PV power, 24V 1a,b)	400 W (MPPT range 30 V to 70 V)
Automatic load disconnect	Yes, maximum load 15 A
Maximum PV open circuit voltage	75 V
Peak efficiency	98 %
Self consumption	10 mA
Charge voltage 'absorption'	14,4 V / 28,8 V
Charge voltage 'float'	13,8 V / 27,6 V
Charge algorithm	multi-stage adaptive
Temperature compensation	-16 mV / °C resp32 mV / °C
Continuous/peak load current	15A / 50A
Low voltage load disconnect	11,1 V / 22,2 V or 11,8 V / 23,6 V or BatteryLife algorithm
Low voltage load reconnect	13,1 V / 26,2 V or 14 V / 28 V or BatteryLife algorithm
Protection	Battery reverse polarity (fuse) Output short circuit Over temperature
Operating temperature	-30 to +60°C (full rated output up to 40°C)
Humidity	100 %, non-condensing
	ENCLOSURE
Colour	Blue (RAL 5012)
Power terminals	6 mm² / AWG10
Protection category	IP65 (electronic components)
Weight	0,5 kg
Dimensions (h x w x d)	100 x 105 x 40 mm
1a) If more PV power is connected, the co 1b) PV voltage must exceed Vbat + 5V for Vbat + 1V	ntroller will limit input power to 200W resp. 400W the controller to start. Thereafter minimum PV voltage is



BLUESOLAR CHARGE CONTROLLERS MPPT 150/70



Solar charge controller MPPT 150/70

Charge current up to 70 A and PV voltage up to 150 V

The BlueSolar 150/70-MPPT charge controller is able to charge a lower nominal-voltage battery from a higher nominal voltage PV array.

The controller will automatically adjust to a 12, 24, 36, or 48 V nominal battery voltage.

Ultra fast Maximum Power Point Tracking (MPPT)

Especially in case of a clouded sky, when light intensity is changing continuously, an ultra fast MPPT controller will improve energy harvest by up to 30% compared to PWM charge controllers and by up to 10% compared to slower MPPT controllers.

Advanced Maximum Power Point Detection in case of partial shading conditions

If partial shading occurs, two or more maximum power points may be present on the power-voltage curve.

Conventional MPPT's tend to lock to a local MPP, which may not be the optimum MPP. The innovative BlueSolar algorithm will always maximize energy harvest by locking to the optimum MPP.

Outstanding conversion efficiency

No cooling fan. Maximum efficiency exceeds 98%. Full output current up to 40°C (104°F).

Flexible charge algorithm

Several preprogrammed algorithms. One programmable algorithm. Manual or automatic equalisation. Battery temperature sensor. Battery voltage sense option.

Programmable auxiliary relay

For alarm or generator start purposes

Extensive electronic protection

Over-temperature protection and power derating when temperature is high. PV short circuit and PV reverse polarity protection.

BlueSolar charge controller	MPPT 150/70
Nominal battery voltage	12 / 24 / 36 / 48V Auto Select
Rated charge current	70A @ 40 °C (104 °F)
Maximum solar array input power	12V: 1000W / 24V: 2000W / 36V: 3000W / 48V: 4000W
Maximum PV open circuit voltage	150V
Minimum PV voltage	Battery voltage plus 7 Volt to start Battery voltage plus 2 Volt operating
Standby power consumption	12V: 0,55W / 24V: 0,75W / 36V: 0,90W / 48V: 1,00W
Efficiency at full load	12V: 95% / 24V: 96,5% / 36V: 97% / 48V: 97,5%
Absorption charge	14.4 / 28.8 / 43.2 / 57.6V
Float charge	13.7 / 27.4 / 41.1 / 54.8V
Equalization charge	15.0 / 30.0 / 45 / 60V
Remote battery temperature sensor	Yes
Default temperature compensation setting	-2,7mV/°C per 2V battery cell
Programmable relay	DPST AC rating: 240VAC/4A DC rating: 4A up to 35VDC, 1A up to 60VDC
CAN bus communication port	Two RJ45 connectors, NMEA2000 protocol
Operating temperature	-40 ℃ to 60 ℃ with output current derating above 40 ℃
Cooling	Natural Convection
Humidity (non condensing)	Max. 95%
Terminal size	35mm² / AWG2
Material & color	Aluminium, blue RAL 5012
Protection class	IP20
Weight	4,2 kg
Dimensions (h x w x d)	350 x 160 x 135 mm
Mounting	Vertical wall mount Indoor only
Safety	EN60335-1
EMC	EN61000-6-1, EN61000-6-3

BLUESOLAR CHARGE CONTROLLERS

BlueSolar 12/24-PWM

ictron energy

Low cost PWM controller.

Internal temperature sensor.

- Three stage battery charging (bulk, absorption, float).
- Protected against over current. _
- Protected against short circuit.
- Protected against reverse polarity connection of the solar panels and/or battery.
- _ With low voltage load disconnect output.
- Optional remote display (20A model only)

BlueSolar DUO 12/24-20

20A at 12V or 24V *

- PWM controller.
- Charges two separate batteries. For example the starter battery and the service battery of a boat or mobile home.

Three models: 5A, 10A or 20A at 12V or 24V *

- Programmable charge current ratio (standard setting: equal current to both batteries).
- Charge voltage settings for three battery types (Gel, AGM and Flooded).
- Internal temperature sensor and optional remote temperature sensor.
- Protected against over current.
- _ Protected against short circuit.
- Protected against reverse polarity connection of the solar panels and/or battery.

- for BlueSolar DUO 12/24-20



40A at 12V or 24V *

BlueSolar MPPT 12/24-40 Maximum Power Point Tracking (MPPT) controller. Increases charge current by up to 30% compared to a PWM controller.

- Charge voltage settings for eight battery types, plus two equalize settings.
- Remote temperature sensor.
 - Protected against over current.
- Protected against short circuit.
- Protected against reverse polarity connection of the solar panels and/or battery.
- With low voltage load disconnect output.

BlueSolar MPPT 12/24-40

- * For 12V use 36 cells solar panels For 24V use 72 cells solar panels



BlueSolar 12/24-10



BlueSolar DUO 12/24-20

.....

Two remote displays: - for BlueSolar 12/24-20



BLUESOLAR CHARGE CONTROLLERS

BlueSolar	BlueSolar 12/24-5 BlueSolar 12/24-10 BlueSolar 12/24-20		BlueSolar DUO 12/24-20		BlueSolar MPPT 12/24-40		
	12V 24V 12V 24V 12V		12V	24V			
Battery Voltage	12/24V Auto Select (2)		12/24V Auto Select (2)		12/24V Aut	o Select (2)	
Rated charge current	5/10/20A		20A		40A		
MPPT Tracking	No		No		Yes		
Second battery output	N	0	Yes		No		
Automatic load disconnect	Yes (maximum load 10/10/20A)		n. a.		Yes (maximum load 15A)		
Maximum solar voltage	28/55	V (2)	28/55	V (2)	28/55	28/55V (2)	
Self-consumption	6m	nA	4m	4mA		10mA	
Default settings							
Absorption charge (1)	14.4V	28.8V	14.4V	28.8V	14.4V	28.8V	
Float charge (1)	13.7V	27.4V	13.7V	27.4V	13.7V	27.4V	
Equalization charge	n.	a.	n. a	a.	15.0V	30.0V	
Over charge disconnect	n.	a.	n. a	a.	14.8V	29.6V	
Over charge recovery	n.	a.	n. a	a.	13.6V	27.2V	
Low voltage load disconnect	11.1V	22.2V	n. a	a.	10.8V	21.6V	
Low voltage load reconnect	12,6V	25.2V	n. a	a.	12.3V	24.6V	
Enclosure & Environmental			X				
Battery temperature sensor	Yes Internal sensor		Yes Internal sensor		Yes Remote sensor		
Temperature compensation	-30mV/℃	-60mV/℃	-30mV/℃	-60mV/℃	-30mV/℃	-60mV/°C	
Operating temperature	-35℃ to +55	℃ (full load)	-35℃ to +55°	℃ (full load)	0-40 <i>°</i> C 40-60 <i>°</i> C	(full load) (derating)	
Cooling	Natural Co	onvection	Natural Convection		Natural Convection		
Humidity (non condensing)	Max. 95%		Max. 95%		Max. 95%		
Protection class	IP20		IP20		IP20		
Terminal size	6mm² / /	AWG10	6mm² / A	AWG10	8mm² /	AWG8	
Weight	160/160)/180gr	180	lgr	140	10gr	
Dimension (h x w x d)	70x133x34 mm 70x133x34 mm 76x153x37 mm		76x153x37 mm		202x66x140 mm		
Mounting	Vertical w Indoor	all mount r only	Vertical wall mount Indoor only		Vertical wall mount Indoor only		
Standards							
Safety			EN603	35-1			
EMC			EN61000-6-1, EN61000-6-3				

BlueSolar 12/24-20, DUO 12/24-20 and BlueSolar MPPT 12/24-40: Other settings possible (see manual)
 For 12V use 36 cell Solar panels

For 12V use 36 cell Solar panels For 24V use 72 cell Solar panels



Maximum Power Point Tracking

Upper curve:

Output current (I) of a solar panel as function of output voltage (V). The maximum power point (MPP) is the point Pmax along the curve where the product I x V reaches its peak.

Lower curve:

Output power $P = I \times V$ as function of output voltage.

When using a PWM (not MPPT) controller the output voltage of the solar panel will be nearly equal to the voltage of the battery, and will be lower than VMP.

12,8 VOLT LITHIUM IRON PHOSPHATE BATTERIES



12,8V 90Ah LiFePO4 battery LFP-B 12,8/90



12,8V 60Ah LiFePO4 battery LFP-B 12,8/60

Why lithium-iron phosphate?

Lithium-iron-phosphate (LiFePO4 or LFP) is the safest of the mainstream li-ion battery types. The nominal voltage of a LFP cell is 3,2V (lead-acid: 2V/cell). A 12,8V LFP battery therefore consists of 4 cells connected in series; and a 25,6V battery consists of 8 cells connected in series.

Rugged

A lead-acid battery will fail prematurely due to sulfation if:

- If it operates in deficit mode during long periods of time (i. e. if the battery is rarely, or never at all, fully charged).
- If it is left partially charged or worse, fully discharged (yacht or mobile home during winter time).

A LFP battery does not need to be fully charged. Service life even slightly improves in case of partial charge instead of a full charge. This is a major advantage of LFP compared to lead-acid. Other advantages are the wide operating temperature range, excellent cycling performance, low internal resistance and high efficiency (see below).

LFP is therefore the chemistry of choice for very demanding applications.

Efficient

In several applications (especially off-grid solar and/or wind), energy efficiency can be of crucial importance. The round trip energy efficiency (discharge from 100% to 0% and back to 100% charged) of the average lead-acid battery is 80%.

The round trip energy efficiency of a LFP battery is 92%.

The charge process of lead-acid batteries becomes particularly inefficient when the 80% state of charge has been reached, resulting in efficiencies of 50% or even less in solar systems where several days of reserve energy is required (battery operating in 70% to 100% charged state).

In contrast, a LFP battery will still achieve 90% efficiency under shallow discharge conditions.

Size and weight

Saves up to 70% in space Saves up to 70% in weight

Expensive?

LFP batteries are expensive when compared to lead-acid. But in demanding applications, the high initial cost will be more than compensated by longer service life, superior reliability and excellent efficiency.

Endless flexibility

LFP batteries are easier to charge than lead-acid batteries. The charge voltage may vary from 14V to 16V (as long as no cell is subjected to more than 4,2V), and they do not need to be fully charged. Therefore several batteries can be connected in parallel and no damage will occur if some batteries are less charged than others.

With or without cell balancing and BMS?

Important facts:

1. A LFP cell will be destroyed <u>immediately</u> if the voltage over the cell falls to less than 2,5V.

2. A LFP cell will be destroyed <u>immediately</u> if the voltage over the cell increases to more than 4,2V. Lead-acid batteries will eventually also be damaged when discharged too deeply or overcharged, but not immediately. A lead-acid battery will recover from total discharge even after it has been left in discharged state during days or weeks (depending on battery type and brand).

3. The cells of a LFP battery <u>do not auto-balance</u> at the end of the charge cycle.

The cells in a battery are not 100% identical. Therefore, when cycled, some cells will be fully charged or discharged earlier than others. The differences will increase if the cells are not balanced/equalized from time to time.

In a lead-acid battery a small current will continue to flow even after one or more cells are fully charged (the main effect of this current is decomposition of water into hydrogen and oxygen). This current helps to fully charge other cells that are lagging behind, thus equalizing the charge state of all cells.

The current through a LFP cell however, when fully charged, is nearly zero, and lagging cells will therefore not be fully charged. The differences between cells may become some so extreme over time that, even though the overall battery voltage is within limits, some cells will be destroyed due to over- or under-voltage.

Low capacity LFP cells can be produced with extremely tight tolerances, so that in case of light duty applications a few cells in series can be, and are, used without active cell balancing.



12,8 VOLT LITHIUM IRON PHOSPHATE BATTERIES

Without cell balancing: 12,8V LFP batteries for light duty applications

In applications were excessive discharge (to less than 11V), overcharge (to more than 15V) or excessive charge/discharge current will never occur, 12,8V batteries with preselected identical cells may be used (available in 60Ah and 90Ah, see battery data). Please note that these batteries are <u>not</u> suitable for series or parallel connection.

Notes:

- 1. A Battery Protect module (see www.victronenergy.com) may be used to prevent excessive discharge.
- 2. The current draw of inverters and inverter/chargers is often still significant (o,1A or more) after low voltage shutdown. The remaining stand-by current will therefore damage the battery if the inverters or inverter/chargers are left connected to the battery after low voltage shutdown during a long period of time.

With cell balancing: 12,8V LFP batteries for heavy duty applications and parallel/series connection

The batteries with suffix B are fitted with integrated Balancing, Temperature and Voltage control (BTV). Up to ten batteries can be paralleled and up to four batteries can be series connected (BTV's are simply daisy-chained) so that a 48V battery bank of up to 900Ah can be assembled. The daisy-chained BTV's must be connected to a battery management system (BMS).

Battery Management System (BMS)

The BMS connects to the BTV's and its essential functions are:

- 1. Disconnect or shut down the load whenever the voltage of a battery cell falls to less than 2,5V.
- 2. Stop the charging process whenever the voltage of a battery cell increases to more than 4,2V.
- 3. Shut down the system whenever the temperature of cell exceeds 50 °C.

More features may be included: see the individual BMS datasheets.

Battery specification		
VOLTAGE AND CAPACITY	LFP-B	LFP-B
	12,8/60	12,8/90
Nominal voltage	12,8V	12,8V
Nominal capacity @ 25°C*	60Ah	90Ah
Nominal capacity @ 0°C*	48Ah	72Ah
Nominal capacity @ -20°C*	30Ah	45Ah
Nominal energy @ 25°C*	768Wh	1152Wh
CYCLE LIFE		
80% DoD	2000	cycles
70% DoD	3000	cycles
50% DoD	5000	cycles
*Discharge current ≤1C		
DISCHARGE		
Maximum continuous discharge current	180A	270A
Recommended continuous discharge current	≤60A	≤90A
Maximum 10 s pulse current	600A	900A
End of discharge voltage	11V	11V
OPERATING CONDITIONS		
Operating temperature	-20 - 50°C	
Storage temperature	-45 - 70°C	
Humidity (non condensing)	Max. 95%	
Protection class	IP 54	
CHARGE		
Charge voltage	14,4V	14,4V
Float voltage	13,6V	13,6V
Maximum charge current	180A	270A
Recommended charge current	≤30A	≤45A
OTHER		
Max storage time @ 25 ℃*	1 y	ear
Dimensions (hxwxd) mm	235x293x139	249x293x168
Weight	12kg	16kg
*When fully charged		



BMS 12/200 FOR 12,8 VOLT LITHIUM IRON PHOSPHATE BATTERIES

Especially designed for vehicles and boats



12,8V 90Ah LiFePO4 battery



12,8V 60Ah LiFePO4 battery



BMS 12/200 with:

- 12V 200A load output, short-circuit proof
- Li-ion battery over-discharge protection
- starter battery discharge protection
- adjustable alternator current limit
- remote on-off switch

Why lithium-iron phosphate?

Lithium-iron-phosphate (LiFePO4 or LFP) is the safest of the mainstream li-ion battery types. The nominal voltage of a LFP cell is 3,2V (lead-acid: 2V/cell). A 12,8V LFP battery therefore consists of 4 cells connected in series; and a 25,6V battery consists of 8 cells connected in series.

Why a Battery Management System (BMS) is needed:

1. A LFP cell will be destroyed immediately if the voltage over the cell falls to less than 2,5V.

2. A LFP cell will be destroyed <u>immediately</u> if the voltage over the cell increases to more than 4,2V. Lead-acid batteries will eventually also be damaged when discharged too deeply or overcharged, but not immediately. A lead-acid battery will recover from total discharge even after it has been left in discharged state during days or weeks (depending on battery type and brand).

3. The cells of a LFP battery <u>do not auto-balance</u> at the end of the charge cycle.

The cells in a battery are not 100% identical. Therefore, when cycled, some cells will be fully charged or discharged earlier than others. The differences will increase if the cells are not balanced/equalized from time to time.

In a lead-acid battery a small current will continue to flow even after one or more cells are fully charged (the main effect of this current is decomposition of water into hydrogen and oxygen). This current helps to fully charge other cells that are lagging behind, thus equalizing the charge state of all cells.

The current through a LFP cell however, when fully charged, is nearly zero, and lagging cells will therefore not be fully charged. The differences between cells may become some so extreme over time that, even though the overall battery voltage is within limits, some cells will be destroyed due to over- or under-voltage.

A LFP battery therefore must be protected by a BMS that actively balances the individual cells and prevents under- and over-voltage.

Rugged

A lead-acid battery will fail prematurely due to sulfation if:

- If it operates in deficit mode during long periods of time (the battery is rarely, or never at all, fully charged).
- If it is left partially charged or worse, fully discharged (yacht or mobile home during winter time).

A LFP battery does not need to be fully charged. Service life even slightly improves in case of partial charge instead of a full charge. This is a major advantage of LFP compared to lead-acid. Other advantages are the wide operating temperature range, excellent cycling performance, low internal resistance and high efficiency (see below).

LFP is therefore the chemistry of choice for very demanding applications.

Efficient

In several applications (especially off-grid solar and/or wind), energy efficiency can be of crucial importance. The round trip energy efficiency (discharge from 100% to 0% and back to 100% charged) of the average lead-acid battery is 80%.

The round trip energy efficiency of a LFP battery is 92%.

The charge process of lead-acid batteries becomes particularly inefficient when the 80% state of charge has been reached, resulting in efficiencies of 50% or even less in solar systems where several days of reserve energy is required (battery operating in 70% to 100% charged state).

In contrast, a LFP battery will still achieve 90% efficiency under shallow discharge conditions.

Size and weight

Saves up to 70% in space Saves up to 70% in weight

Expensive?

LFP batteries are expensive when compared to lead-acid. But in demanding applications, the high initial cost will be more than compensated by longer service life, superior reliability and excellent efficiency.

Endless flexibility

LFP batteries are easier to charge than lead-acid batteries. The charge voltage may vary from 14V to 16V (as long as no cell is subjected to more than 4,2V), and they do not need to be fully charged. Therefore several batteries can be connected in parallel and no damage will occur if some batteries are less charged than others. We therefore designed two 12,8V batteries with integrated Balancing, Temperature and Voltage control (BTV), of respectively 60Ah and 90Ah. Our 12V BMS will support up to 10 batteries in parallel (BTV's are simply daisy-chained) so that a 12V battery bank of up to 900Ah can be assembled.



BMS 12/200 FOR 12,8 VOLT LITHIUM IRON PHOSPHATE BATTERIES

A 12V BMS that protects the alternator (and wiring), and supplies up to 200A in any DC load (including inverters and inverter/chargers)

Alternator/battery charger input (Power Port AB)

- 1. The first function of Power Port AB is to prevent the load connected to the LFP battery from discharging the starter battery. This function is similar to that of a Cyrix battery combiner or Argo FET battery isolator. Current can flow to the LFP battery only if the input voltage (= voltage on the starter battery) exceeds 13V.
- 2. Current cannot flow back from the LFP battery to the starter battery, thus preventing eventual damage to the LFP battery due to excessive discharge.
- 3. Excessive input voltage and transients are regulated down to a safe level.
- 4. Charge current is reduced to a safe level in case of cell unbalance or over temperature.
- 5. The input current is electronically limited to approximately 80% of the AB fuse rating. A 50A fuse, for example, will therefore limit the input current to 40A. Choosing the right fuse will therefore:
 - a. Protect the LFP battery against excessive charge current (important in case of a low capacity LFP battery).
 - b. Protect the alternator against overload in case of a high capacity LFP battery bank (most 12V alternators will overheat and fail if running at maximum output during more than 15 minutes).
 - c. Limit charge current in order not to exceed the current handling capability of the wiring.

The maximum fuse rating is 100A (limiting charge current to approximately 80A).

Load/battery charger output/input (Power Port LB)

- 1. Maximum current in both directions: 200A continuous.
- 2. Peak discharge current electronically limited to 400A.
- 3. Battery discharge cut-off whenever the weakest cell falls below 3V.
- 4. Charge current is reduced to a safe level in case of cell unbalance or over temperature.

VOLTAGE AND CAPACITY	LFP 12,8/60	LFP 12,8/90
Nominal voltage	12,8V	12,8V
Nominal capacity @ 25°C*	60Ah	90Ah
Nominal capacity @ 0°C*	48Ah	72Ah
Nominal capacity @ -20°C*	30Ah	45Ah
Nominal energy @ 25°C*	768Wh	1152Wh
Cycle life		
80% DoD	2000	cycles
70% DoD	3000	cycles
50% DoD	5000	cycles
*Discharge current <1C		

Battery speci	ification	
DISCHARGE	LFP 12,8/60	LFP 12,8/90
Maximum continuous discharge current	180A	270A
Recommended continuous discharge current	≤60A	≤90A
Maximum 10 s pulse current	600A	900A
End of discharge voltage	11V	11V
Operating conditions		
Operating temperature	-20 - 50°C	
Storage temperature	-45 - 70°C	
Humidity (non condensing)	Max. 95%	
Protection class	IP	54

CHARGE		LFP 12,8/60)	LFP 12,8/90
Charge voltage		14,4V		14,4V
Float voltage		13,6V		13,6V
Maximum charge current		180A		270A
Recommended charge cu	rrent	≤30A		≤45A
Other				
Max storage time @ 25 °C*			1	year
Dimensions (hxwxd) mm	235x2	93x139	2	49x293x168
Weight		12kg		16kg
*When fully charged				

BMS 12/200 specificati	on
Maximum number of 12,8V batteries	10
Maximum charge current, Power Port AB	80A @ 40°C
Maximum charge current, Power Port LB	200A @ 40°C
Maximum continuous discharge current, LB	200A @ 40°C
Peak discharge current, LB (short circuit proof)	400A
Approximate cut-off voltage	11V
GENERAL	
No load current when operating	10mA
Current consumption when switched off	5mA
Current consumption after battery discharge cut-off due to low cell voltage	3mA
Operating temperature range	-40 to +60°C
Humidity, maximum	100%
Humidity, average	95%
Protection, electronics	IP65
DC connection AB, LB and battery minus	M8
DC connection battery plus	Faston female
	6.3 mm
LED's	
Battery being charged through Power Port AB	green
Battery being charged through Power Port LB	green
Power port LB active	green
Over temperature	red
ENCLOSURE	
Weight (kg)	1,8
Dimensions (hxwxd in mm)	65 x 120 x 260
STANDARDS	
Emission	EN 50081-1
Immunity	EN 50082-1
Automotive Directive	2004/104/EC



Up to ten 12,8V LFP batteries can be connected in parallel Isolated Orion DC-DC converter needed for DC loads with minus connected to chassis

24V 180AH LITHIUM-ION BATTERY AND LYNX-ION



24V 180Ah Lithium-ion battery



Lynx Ion



Ion control: Main screen



Ion control: History screen

Lynx Ion Status		
State	Running	
System Switch	Enabled	
Balancing	Disabled	
	_	
ion control		

Ion control: Lynx Ion Status

- High energy density: more energy with less weight;
- High charge currents (shortens the charge period);
- High discharge currents (enabling for example electrical cooking on a small battery bank);
- Long battery life (up to six times the battery life of a conventional battery);
- High efficiency between charging and discharging (very little energy loss due to heat development);
- Higher continuous power available.

Why Lithium-iron phosphate?

Lithium-iron-phosphate (LiFePO4 or LFP) is the safest of the mainstream Li-ion battery types. The nominal voltage of a LFP cell is 3,2V (lead-acid: 2V/cell). A 25,6V LFP battery consists of 8 cells connected in series.

The advantages of the Victron Lynx Lithium-ion battery system

The modular system used adds below advantages:

- The Victron Lithium-ion battery system is easy to install due to its modularity. No complicated wiring diagrams are required.
- Detailed information is available on the waterproof Ion Control display.
- The 350A relay in the Lynx lon provides maximum safety: in case the chargers or loads do not listen to the commands from the Lynx lon, the main safety relay will open to prevent permanent damage to the batteries.
- For typical marine installations there is an extra smaller output, so you can still power the bilge pump and disconnect all other house loads by opening the 350A relay.

Complete system

A complete system consists of:

- One or more 24V 180Ah Lithium-Ion batteries.
- (optional) The Lynx Power In, a modular dc bus bar.
- The Lynx Ion is the battery management system (BMS) that controls the batteries. A 350 Ampère safety contactor is inside the Lynx Ion.
- The Lynx Shunt VE.Can, a battery monitor including the main fuse. Note that the fuse needs to be
 purchased separately.
- (optional) The Lynx Distributor, a DC distribution system with fuses.
- (optional) The **Ion Control**, a digital control panel.

24V 180Ah Lithium-Ion Batteries

The base of the Victron Lithium-ion battery system is formed by individual 24V/180Ah Lithium-ion batteries. They have a built-in Cell Management System (BMS) which protects the battery on a cell level. It monitors individual cell voltage and system temperature, and actively balances the individual cells. All measured parameters are sent to the Lynx Ion which monitors the system as a whole.

Lynx lon

The Lynx Ion is the BMS. It contains the 350A safety contactor, and controls the cell-balancing, charging and discharging of the system. The Lynx Ion will protect the battery pack from both overcharging and depletion. When an overcharge is imminent, it will signal the charging devices to decrease or stop charging. This is done with the VE.Can bus (NMEA2000) compatible, and also via the two available open/close contacts. Same when the battery is nearing empty, and there is no charging capability available. It will signal big loads to switch off.

For both over charging and depletion there is a last safety resort, the built-in 350A contactor. In case signaling etcetera does not stop the imminent overcharge or depletion, it will open the contactor.

NMEA2000 Canbus

Communication with the outside world is done via the VE.Can protocol.

Ion Control

See the separate Ion Control datasheet for more information on the display.


24V 180AH LITHIUM-ION BATTERY AND LYNX-ION

Lithium-ion 24V 180Ah 4.75kWh battery							
Technology	Lithium iron phosphate (LiFePo4)						
Nominal voltage	26,4 V						
Nominal capacity	180 Ah						
Nominal power	4,75 KWh						
Weight	55 kg						
Power/Weight ratio	86 Wh/kg						
Dimensions (LxWxH)	620 x 188 x 360 mm						
Charge cut-off voltage at 0.05C	28,8 V						
Discharge cut-off voltage	20 V						
Recommended charge/discharge current	54 A (0,3C)						
Maximum charge current (1C)	180 A						
Maximum discharge current (1.5C)	270 A						
Pulse discharge current (10s)	1000 A						
Cycle Life @80% DOD (0.3C)	2000						
Series configuration	Yes, up to 2 (more in series on request)						
Parallel configuration	Yes, easy up to 4 (more parallel on request)						
Operating temp. charge	0~45 °C						
Operating temp. discharge	-20~55 ℃						
Storage temp.	-20~45 °C						

Lynx Ion	
Maximum number batteries in series	2
Maximum number batteries in parallel	8
Enclosure	
Weight	1,4 kg
Dimensions (LxWxH)	190 x 180 x 80 mm
IO	
Safety contactor	350 A
Bilge pump contactor maximum current	10 A
External relay contactor maximum current	10 A
Charged-signal contact	1A @ 60VDC
Discharged-signal contact	1A @ 60VDC
Standards	
Emission	EN 50081-1
Immunity	EN 50082-1

Block diagram Lithium-ion battery system





ION CONTROL



Main screen



History screen



Diagnostics screen



Lynx Ion Status screen



Back side

Ion Control

The Ion Control shows all vital data from the Lithium Battery system:

- Battery voltage (V).
- Battery charge/discharge current (A).Ampere-hours consumed (Ah).
- Ampere-nours consumed
- State of charge (%).
- Time to go at the current rate of discharge until the battery has reached 90% discharge.
- Visual alarm: almost charged, almost discharged

Historic data

It will also show the following historic values:

- The depth of the deepest discharge.
- The number of full discharges
- The cumulative number of Amp hours drawn from the battery
- The minimum battery voltage recorded
- The maximum battery voltage recorded

The historic values are stored in non-volatile memory in the Lynx Shunt in the system.

Using multiple Ion Controls

Multiple Ion Controls can be installed to monitor a single Lithium Battery System. All Ion Controls will display to same data. It is recommended, when more than one Ion Control is installed, to use an external network power source due to the limited capacity of the Lynx Shunt's power supply.

Note that per system only one Lynx lon module can be installed.

ELECTRICAL							
Power supply voltage range	10 – 32 VDC (No need for an external power supply. Power is supplied on the VE.Can RJ network by the Lynx Shunt)						
Power consumption	130mA at 12VDC						
Audible Alarm	4kHz Internal sounder						
Connections	Integral Deutsch 12 way connector (DT04-12PA)						
Cabling supplied	1m Deutsch 12 way to Victron RJ45 Canbus connection						
Communications	NMEA2000 (expects battery instance 0)						
ENVIRONMENTAL							
Operating temperature	-25 to +75°C						
Degree of Protection	IP67						
Salt Spray	IEC 60068-2-52: 1996						
EMC	IEC 61000 and EN55022						
	ENCLOSURE						
Material & Colour	Anthracite Grey ABS housing and acrylic lens						
Dimensions	110mm x 110mm x 38.5mm deep (without connector)						
Depth front mounted	21.5mm forward protrusion, 17mm rear protrusion (without connector)						
Panel cut out	64mm diameter hole with 4 mount holes, 4.3mm dia.						
Weight	265 grams						





ION CONTROL

Modes of operation



Browsing

To browse through the screens the keys [D] and [B] are used. Press [D] to continue to the next screen and press [B] to go to the previous screen.

Lighting and contrast

To enter this menu press [C], a popup window will appear. Use [A] and [B] to alter the intensity of the backlight. The LCD contract can be changed using [D] and [E].

Pressing [C] will store the settings and exit the menu.

System diagram





ION CONTROL



















AGM battery 12V 90Ah



GEL OPzV 2V cells battery

1. VRLA technology

VRLA stands for Valve Regulated Lead Acid, which means the batteries are sealed. Gas will escape through the safety valves only in case of overcharging or cell failure. VRLA batteries are maintenance free for life.

2. Sealed (VRLA) AGM batteries

AGM stands for Absorbent Glass Mat. In these batteries the electrolyte is absorbed into a glass-fibre mat between the plates by capillary action. As explained in our book 'Energy Unlimited', AGM batteries are more suitable for short-time delivery of very high currents (engine starting) than gel batteries.

3. Sealed (VRLA) Gel batteries

Here the electrolyte is immobilized as gel. Gel batteries in general have a longer service life and better cycle capacity than AGM batteries.

4. Low Self-discharge

Because of the use of lead calcium grids and high purity materials, Victron VRLA batteries can be stored during long periods of time without recharge. The rate of self-discharge is less than 2% per month at 20°C. The self discharge doubles for every increase in temperature with 10°C.

Victron VRLA batteries can therefore be stored during up to a year without recharging, if kept under cool conditions.

5. Exceptional Deep Discharge Recovery

Victron VRLA batteries have exceptional discharge recovery, even after deep or prolonged discharge. It should however be stressed that repetitive deep discharge and prolonged discharge have a very negative influence on the service life of all lead acid batteries, Victron batteries are no exception.

6. Battery discharging characteristics

The rated capacity of Victron AGM and Gel Deep Cycle batteries refers to 20 hour discharge, in other words: a discharge current of 0,05 C.

The rated capacity of Victron Tubular Plate Long Life batteries refers to 10 hours discharge. The effective capacity decreases with increasing discharge current (see table 1). Please note that the capacity reduction will be even faster in case of a constant power load, such as an inverter.

Discharg time (constant current)	End Voltage V	Ind AGM Gel Itage 'Deep 'Deep Cycle' Cycle' V % %		Gel 'Long Life' %
20 hours	10,8	100	100	112
10 hours	10,8	92	87	100
5 hours	10,8	85	80	94
3 hours	10,8	78	73	79
1 hour	9,6	65	61	63
30 min.	9,6	55	51	45
15 min.	9,6	42	38	29
10 min.	9,6	38	34	21
5 min.	9,6	27	24	
5 seconds		8 C	7 C	

Table 1: Effective capacity as a function of discharge time

(the lowest row gives the maximum allowable 5 seconds discharge current)

Our AGM deep cycle batteries have excellent high current performance and are therefore recommended for high current applications such as engine starting. Due to their construction, Gel batteries have a lower effective capacity at high discharge currents. On the other hand, Gel batteries have a longer service life, both under float and cycling conditions.

7. Effect of temperature on service life

High temperature has a very negative effect on service life. The service life of Victron batteries as a function of temperature is shown in table 2.

Average Temperature	AGM Deep Cycle years	Gel Deep Cycle years	Gel Long Life years
20°C/68°F	7 - 10	12	20
20 ℃ / 68 °F 30 ℃ / 86 °F	7 - 10 4	12 6	20 10

Table 2: Design service life of Victron batteries under float service



8. Effect of temperature on capacity

As is shown by the graph below, capacity reduces sharply at low temperatures.



Fig. 1: Effect of temperature on capacity

9. Cycle life of Victron batteries

Batteries age due to discharging and recharging. The number of cycles depends on the depth of discharge, as is shown in figure 2.



Fig. 2: Cycle life

10. Battery charging in case of cycle use: the 3-step charge curve

The most common charge curve used to charge VRLA batteries in case of cyclic use is the 3-step charge curve, whereby a constant current phase (the bulk phase) is followed by two constant voltage phases (absorption and float), see fig. 3.



Fig. 3: Three step charge curve

During the absorption phase the charge voltage is kept at a relatively high level in order to fully recharge the battery within reasonable time. The third and last phase is the float phase: the voltage is lowered to standby level, sufficient to compensate for self discharge.



Disadvantages of the traditional 3-step charge curve:

- During the bulk phase the current is kept at a constant and often high level, even after the gassing voltage (14,34 V for a 12 V battery) has been exceeded. This can lead to excessive gas pressure in the battery. Some gas will escape trough the safety valves, reducing service life.
- Thereafter the absorption voltage is applied during a fixed period of time, irrespective of how deep the battery has been discharged previously. A full absorption period after a shallow discharge will overcharge the battery, again reducing service life. (a. o. due to accelerated corrosion of the positive plates)
- Research has shown that battery life can be increased by decreasing float voltage to an even lower level when the battery is not in use.

11. Battery charging: longer battery life with Victron 4-step adaptive charging

Victron developed the adaptive charge curve. The 4-step adaptive chare curve is the result of years of research and testing.

The Victron four-step adaptive charge curve solves the 3 main problems of the 3 step curve:

Battery Safe mode

In order to prevent excessive gassing, Victron has invented the 'Battery Safe Mode'. The battery Safe Mode will limit the rate of voltage increase once the gassing voltage has been reached. Research has shown that this will reduce internal gassing to a safe level.

Variable absorption time

Based on the duration of the bulk stage, the charger calculates how long the absorption time should be in order to fully charge the battery. If the bulk time is short, this means the battery was already charged and the resulting absorption time will also be short, whereas a longer bulk time will also result in a longer absorption time.

Storage mode

After completion of the absorption period the battery should be fully charged, and the voltage is lowered to the float or standby level. If no discharge occurs during the next 24 hours, the voltage is reduced even further and the battery goes into storage mode. The lower storage voltage reduces corrosion of the positive plates. Once every week the charge voltage is increased to the absorption level for a short period to compensate for self discharge (Battery Refresh mode).

12. Battery charging in case of standby use: constant voltage float charging

When a battery is not frequently deeply discharged, a 2-step charge curve can be used. During the first phase the battery is charged with a limited current (the bulk phase). Once a preset voltage has been reached the battery is kept at that voltage (the float phase).

This charge method is used for starter batteries in vehicles, and in uninterruptible power supplies (UPS).



13. Optimum charge voltage of Victron VRLA batteries

The recommended charge voltage settings for a 12 V battery are shown in table 3.

Fig. 4: Four-step adaptive charge curve

14. Effect of temperature on charging voltage

The charge voltage should be reduced with increased temperature. Temperature compensation is required when the temperature of the battery is expected to be less than 10°C / 50°F or more than 30°C / 85°F during long periods of time. The recommended temperature compensation for Victron VRLA batteries is -4 mV / Cell (-24 mV /°C for a 12 V battery). The centre point for temperature compensation is 20°C / 70°F.

15. Charge current

The charge current should preferably not exceed 0,2 C (20 A for a 100 Ah battery). The temperature of a battery will increase by more than 10°C if the charge current exceeds 0,2 C. Therefore temperature compensation is required if the charge current exceeds 0,2 C.



	Float Service (V)	Cycle service Normal (V)	Cycle service Fastest recharge (V)							
Victron AGM "De	Victron AGM "Deep Cycle"									
Absorption		14,2 - 14,6	14,6 - 14,9							
Float	13,5 - 13,8	13,5 - 13,8	13,5 - 13,8							
Storage	13,2 - 13,5	13,2 - 13,5	13,2 - 13,5							
Victron Gel "Dee	o Cycle"									
Absorption		14,1 - 14,4								
Float	13,5 - 13,8	13,5 - 13,8								
Storage	13,2 - 13,5	13,2 - 13,5								
Victron Gel "Long	g Life″									
Absorption		14,0 - 14,2								
Float	13,5 - 13,8	13,5 - 13,8								
Storage	13,2 - 13,5	13,2 - 13,5								

Table 3: Recommended charge voltage

12 Volt Deep Cycle	AGM	General Specification							
Article number	۸b	V	l x w x h mm	Weight kg	CCA @0°F	RES CAP @80°F	Technology: flat plate AGM Terminals: copper		
BAT406225080	240	6	320x176x247	31	1500	480	Rated capacity: 20 hr discharge at 25 ℃		
BAT212070080	8	12	151x65x101	2,5			Float design life: 7-10 years at 20 °C		
BAT212120080	14	12	151x98x101	4,1			400 cycles at 80% discharge		
BAT212200080	22	12	181x77x167	5,8			600 cycles at 50% discharge		
BAT412350080	38	12	197x165x170	12,5			1000 cycles at 30 % discharge		
BAT412550080	60	12	229x138x227	20	450	90			
BAT412600080	66	12	258x166x235	24	520	100			
BAT412800080	90	12	350x167x183	27	600	145			
BAT412101080	110	12	330x171x220	32	800	190			
BAT412121080	130	12	410x176x227	38	1000	230			
BAT412151080	165	12	485x172x240	47	1200	320			
BAT412201080	220	12	522x238x240	65	1400	440			

12 Volt Deep Cycle	GEL	General Specification					
Article number	Ah	v	l x w x h mm	Weight kg	CCA @0℉	RES CAP @80°F	Technology: flat plate GEL Terminals: copper
BAT412550100	60	12	229x138x227	20	300	80	Rated capacity: 20 hr discharge at 25 °C
BAT412600100	66	12	258x166x235	24	360	90	Cycle design life: 12 years at 20 °C
BAT412800100	90	12	350x167x183	26	420	130	500 cycles at 80% discharge
BAT412101100	110	12	330x171x220	33	550	180	750 cycles at 50% discharge
BAT412121100	130	12	410x176x227	38	700	230	Tood cycles at 00% discharge
BAT412151100	165	12	485x172x240	48	850	320	
BAT412201100	220	12	522x238x240	66	1100	440	

2 Volt Long Life GEL					General Specification		
Article number	Ah	v	lxbxh mm	Weight kg	Technology: tubular plate GEL Terminals: copper		
BAT702601260	600	2	145x206x688	49	Rated capacity: 10 hr discharge at 25 °C		
BAT702801260	800	2	210x191x688	65	Cycle design life: 20 years at 20 °C		
BAT702102260	1000	2	210x233x690	80	1500 cycles at 80% discharge		
BAT702122260	1200	2	210x275x690	93	2500 cycles at 50% discharge		
BAT702152260	1500	2	210x275x840	115	4000 Cycles at 50% discharge		
BAT702202260	2000	2	215x400x815	155			
BAT702252260	2500	2	215x490x815	200			
BAT702302260	3000	2	215x580x815	235			

Other capacities and terminal types: at request

BLUESOLAR MONOCRYSTALLINE PANELS

1	M	DE	M	hſ	hſ	D
Ì		1			hi	Ď
Ì	11	11				ĥ
Ì	hi	h				ĥ
ì	i.	1				6
ì	i.	Ń				ĥ
ì	Ĥ	i.	1	1		ĥ
ì	i.	i.				ĥ
ì	i.	1				ĥ
ì	Ĥ	i.	11			ĥ
Ì	h	h			1	ň
Ì	h	Ĥ				ĥ

ictron energy

- Low voltage-temperature coefficient enhances high-temperature operation.
- Exceptional low-light performance and high sensitivity to light across the entire solar spectrum.
- 25-year limited warranty on power output and performance.
 - 2-year Limited warranty on materials and workmanship.
- Sealed, waterproof, multi-functional junction box gives high level of safety.
- High performance bypass diodes minimize the power drop caused by shade.
- Advanced EVA (Ethylene Vinyl Acetate) encapsulation system with triple-layer back sheet meets the most stringent safety requirements for high-voltage operation.
- A sturdy, anodized aluminum frame allows modules to be easily roof-mounted with a variety of standard mounting systems.
- Highest quality, high-transmission tempered glass provides enhanced stiffness and impact resistance.
- Pre wired quick-connect system with MC4 (PV-ST01) connectors. (Except for the 30W panel)



20 panels

BlueSolar Monocrystalline 280W

MC4 connectors

				Electrical data under STC (1)					
Туре	Module Size	Glass size	Weight	Nominal Power	Max-Power Voltage	Max-Power Current	Open-Circuit Voltage	Short-circuit Current	
				Рмрр	Vmpp	Імрр	Voc	lsc	
Module	mm	mm	Kg	W	V	А	V	А	
SPM30-12	450 x 540 x 25	445 x 535	2.5	30	18	1.67	22.5	2	
SPM50-12	760 x 540 x 35	755 x 535	5.5	50	18	2.78	22.2	3.16	
SPM80-12	1110 x 540 x 35	1105 x 535	8.2	80	18	4.58	22.25	4.98	
SPM100-12	963 x 805 x 35	958 x 800	10.5	100	18	5.56	22.4	6.53	
SPM130-12	1220 x 808 x 35	1214 x 802	13	130	18	7.23	21.6	7.94	
SPM180-24	1580 x 808 x 35	1574 x 802	14.5	180	36	5.01	44.9	5.50	
SPM280-24	1956 x 992 x 50	1950 x 986	20	280	36	7.89	44.25	8.76	
Module		SPM30-12	SPM50-12	SPM80-12	SPM100-12	SPM130-12	SPM180-24	SPM280-24	
Nominal Power (±3%	6 tolerance)	30W	50W	80W	100W	130W	180W	280W	
Cell type		Monocrystalline							
Number of cells in ser	ies			36 72				2	
Maximum system vol	tage (V)			1000V					
Temperature coefficie	ent of PMPP (%)	-0.48/°C	-0.48/°C	-0.48/°C	-0.48/°C	-0.48/°C	-0.48/°C	-0.48/°C	
Temperature coefficie	ent of Voc (%)	-0.34/°C	-0.34/°C	-0.34/°C	-0.34/°C	-0.34/°C	-0.34/°C	-0.34/°C	
Temperature coefficie	ent of lsc (%)	+0.037/°C	+0.037/°C	+0.037/°C	+0.037/°C	+0.05/°C	+0.037/°C	+0.037/°C	
Temperature Range					-40°C to +80°C				
Surface Maximum Loa	ad Capacity				200kg/m ²				
Allowable Hail Load					23m/s, 7.53g				
Junction Box Type		PV-JH03-2	PV-JH02	PV-JH02	PV-JH02	PV-RH0301	PV-JH03	PV-JH200	
Connector Type		No connector	MC4	MC4	MC4	MC4	MC4	MC4	
Length of Cables		450mm	750mm	900mm	900mm	900mm	900mm	1000mm	
Output tolerance					+/-3%				
Frame					Aluminium				
Product warranty					2 years				
Warranty on electrical performance		$10 \text{ years } 90\% \pm 25 \text{ years } 80\% \text{ of nower output}$							

 Smallest packaging unit
 1 panel

 Quantity per pallet
 40 panels
 40 panels
 20 panels
 20 panels
 20 panels

1) STC (Standard Test Conditions): 1000W/m², 25°C, AM (Air Mass) 1.5



BLUESOLAR POLYCRYSTALLINE PANELS



- Low voltage-temperature coefficient enhances high-temperature operation.
- Exceptional low-light performance and high sensitivity to light across the entire solar spectrum.
- 25-year limited warranty on power output and performance.
- 2-year Limited warranty on materials and workmanship.
 - Sealed, waterproof, multi-functional junction box gives high level of safety.
- High performance bypass diodes minimize the power drop caused by shade.
- Advanced EVA (Ethylene Vinyl Acetate) encapsulation system with triple-layer back sheet meets the most stringent safety requirements for high-voltage operation.
- A sturdy, anodized aluminum frame allows modules to be easily roof-mounted with a variety of standard mounting systems.
- Highest quality, high-transmission tempered glass provides enhanced stiffness and impact resistance.
- Pre wired quick-connect system with MC4 (PV-ST01) connectors.



MC4 connectors

BlueSolar Polycrystalline 130W

				Electrical data under STC (1)					
Туре	Module Size	Glass size	Weight	Nominal Power	Max-Power Voltage	Max-Power Current	Open-Circuit Voltage	Short-circuit Current	
				Рмрр	Vmpp	Імрр	Voc	lsc	
Module	mm	mm	Kg	W	V	А	V	А	
SPP30-12	735x350x25	730x345	3.5	30	18	1.66	21.6	1.83	
SPP50-12	610x670x35	605x665	5	50	18	2.85	22.19	3.09	
SPP80-12	950x670x35	945x665	8.2	80	18	4.58	22.25	4.98	
SPP100-12	1150x670x35	1145x665	11.8	100	18	5.72	22.36	6.12	
SPP130-12	1480x680x35	1474x674	12.5	130	18	7.43	22.4	8.02	
SPP280-24	1956x992x50	1950x986	24	280	36	7.89	44.25	8.76	

Module	SPP30-12	SPP50-12	SPP80-12	SPP100-12	SPP130-12	SPP280-24
Nominal Power (±3% tolerance)	30W	50W	80W	100W	130W	280W
Cell type	Polycrystalline					
Number of cells in series	36 72					
Maximum system voltage (V)	1000V					
Temperature coefficient of PMPP (%)	-0.47/°C	-0.47/°C	-0.47/°C	-0.47/°C	-0.47/°C	-0.47/°C
Temperature coefficient of Voc (%)	-0.35/°C	-0.35/°C	-0.34/°C	-0.34/°C	-0.35/°C	-0.35/°C
Temperature coefficient of lsc (%)	+0.05/°C	+0.05/°C	+0.045/°C	+0.045/°C	+0.05/°C	+0.045/°C
Temperature Range	-40°C to +80°C					
Surface Maximum Load Capacity	200kg/m ²					
Allowable Hail Load	23m/s, 7.53g					
Junction Box Type	PV-JH03-2	PV-JH02	PV-JH02	PV-JH02	PV-JH02	PV-JH200
Connector Type	No connector MC4					
Length of Cables	450mm	mm 750mm 900mm			1000mm	
Output tolerance	+/-3%					
Frame	Aluminium					
Product warranty	2 years					
Warranty on electrical performance	10 years 90% + 25 years 80% of power output					
Smallest packaging unit	1 panel					
Quantity per pallet	40 panels	40 panels	20 panels	20 panels	20 panels	20 panels
1) STC (Standard Test Conditions): 1000W/m ³ , 25%C, AM (Air Mass) 1.5						

83



PowerControl: Dealing with limited generator or grid power All models in the MultiPlus range feature powerful battery chargers. When the largest model is working hard it can draw almost 10A from a 230V supply. Using the remote panel it is possible to 'dial-in' the maximum current that is available from mains or generator. The MultiPlus will then automatically regulate the charger taking account of other system AC loads and ensuring the charger only uses what is spare. This way it is possible to avoid tripping the mains power or overloading the generator.

POWER CONTROL ©

Battery charger reduces its output, if required, to avoid overload of supply when system consumption is high.



PowerAssist: Boosting the power available from mains or generator, an innovative feature of Multiplus. The feature that most distinguishes the MultiPlus from other inverter / chargers is PowerAssist. This feature takes the principle of PowerControl to a further dimension by allowing a MultiPlus to supplement the power available from mains or generator to 'assist' during periods of high demand. Peak power demand is almost always sustained only for short periods, either a few minutes (in the case of items like cooking appliances) or just a few seconds (in the case of the burst of energy needed to start an air-conditioning or refrigeration compressor).

With the capacity of the generator or mains power set on the remote panel, the MultiPlus detects when the load is becoming too much for the supply and will instantly provide the extra power required. When the demand has reduced, the unit returns to charging the battery. This feature is equally effective in large and small systems helping to reduce the required generator capacity or to achieve greater things with limited mains power. There is even a special feature to enable the MultiPlus/Quattro to work perfectly with portable generators.

POWER ASSIST ©

Inverter boosts incoming power, if required, to avoid overload of supply when system consumption exceeds supply.





COMFORT SYSTEM

COMFORT PLUS SYSTEM

Appliance	System
Lighting	Quattro 12/3000/120
Communication & navigation	BMV602-S battery monitor
Water heater	2x12V/200AH and 1X80AH batteries
Microwave oven	Digital control remote panel
2 ring introduction hob	Alternator 12/150
Coffee machine/Kettle	DC Link Box
TV/DVD	Isolation transformer
Laptop	Cyrix battery separator
Smal chargers (mobile phone, electric shaver)	
Refrigerator and freezer	Solarpanel and MPTT Solar charger

Appliance	System			
Lighting	2 xQuattro 24/5000/120			
Communication & navigation	VE-NET Battery controller			
Water heater	4x12V/200AH and 1X80AH batteries			
Electric gallery with 4 ring induction hob, microwave/combi oven, refrig- erator, freezer, washer/dryer.	Blue Power panel			
Coffee machine and kettle	Alternator 12/150			
TV/DVD	DC Link box			
Multimedia PC	Isolation transformers			
Small chargers (mobile, phone, shaver etc)				
Modest air-conditioning	Solarpanel and MPTT Solar charger			

COMFORT SYSTEM - 7 KVA (30A) CAPACITY



COMFORT PLUS SYSTEM - 25 KVA CAPACITY



ABOUT VICTRON ENERGY

With over 38 years of experience, Victron Energy enjoys an unrivalled reputation for technical innovation, reliability and quality. Victron is a world leader in the supply of self-supporting electrical power. Our products have been designed to meet the most demanding situations faced by a diversity of craft, recreational and commercial alike. Victron's ability to meet the demand for customized off-grid systems is unprecedented. Our product range includes sine wave inverters and inverter/chargers, battery chargers, DC/DC converters, transfer switches, gel and AGM batteries, alternators, battery monitors, solar charge regulators, solar panels, complete network solutions and many other innovative solutions.

World-wide service and support

Having served the off-grid, industrial and vehicle markets as well as both the commercial and leisure marine sectors for over 38 years, Victron has an established network of dealers and distributors covering the whole world. Our customer base is such that providing prompt and competent local service is essential.

This is reflected in the capabilities of our support network. Our flexible approach to service support and our commitment to quick turnaround for repairs is marketleading. There are countless examples of Victron products that have provided for decades of reliable service in the most demanding applications. This level of reliability combined with the highest level of technical know-how results in Victron Energy power systems that offer the very best value available.













Victron Energy B.V. / De Paal 35 1351 JG Almere / The Netherlands Phone: +31 (0)36 535 97 00 Fax: +31 (0)36 535 97 40 e-mail: sales@victronenergy.com www.victronenergy.com

SAL064136020 REV 09 2013-02